

**Fiche de Données de Sécurité****FASSAFILL EPOXY COMP.A**

Fiche signalétique du 27/09/2023 révision 2

**RUBRIQUE 1 – Identification de la substance/du mélange et de la société/de l'entreprise****1.1. Identificateur de produit**

Identification du mélange:

Dénomination commerciale: FASSAFILL EPOXY COMP.A

Code commercial: 1281

UFI: WDPY-Q5GY-EPDA-SFDT

**1.2. Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées**

Usage recommandé : Mortier époxy à deux composants

Usages déconseillés : Non destiné à l'usage des consommateurs; Pour l'usage professionnel seulement

**1.3. Renseignements concernant le fournisseur de la fiche de données de sécurité**

Fournisseur: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Responsable : laboratorio.spresiano@fassabortolo.it

**1.4. Numéro d'appel d'urgence**

ORFILA (INRS): + 33 ( 0 ) 1 45 42 59 59

**RUBRIQUE 2 – Identification des dangers****2.1. Classification de la substance ou du mélange****Règlement (CE) n° 1272/2008 (CLP)**

Skin Irrit. 2 Provoque une irritation cutanée.

Eye Irrit. 2 Provoque une sévère irritation des yeux.

Skin Sens. 1 Peut provoquer une allergie cutanée.

Aquatic Chronic 3 Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Effets physico-chimiques nocifs sur la santé humaine et l'environnement :

Aucun autre danger

**2.2. Éléments d'étiquetage****Règlement (CE) n° 1272/2008 (CLP)****Pictogrammes de danger et mention d'avertissement**

Attention

**Mentions de danger**

H315 Provoque une irritation cutanée.

H317 Peut provoquer une allergie cutanée.

H319 Provoque une sévère irritation des yeux.

H412 Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

**Conseils de prudence**

P261 Éviter de respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols.

P273 Éviter le rejet dans l'environnement.

P280 Porter des gants de protection et un équipement de protection des yeux/du visage.

P333+P313 En cas d'irritation ou d'éruption cutanée: consulter un médecin.

P337+P313 Si l'irritation oculaire persiste: consulter un médecin.

**Dispositions spéciales:**

EUH205 Contient des composés époxydiques. Peut produire une réaction allergique.

**Contient:**

bis-[4-(2,3-époxypropoxy)phényl]propane  
Formaldehyde, oligomeric reaction products  
with 1-chloro-2,3-epoxypropane and phenol

oxirane, dérivés mono[(C12-14-alkyloxy)  
méthyle]

Reaction mass of bis(1,2,2,6,6-  
pentamethyl-4-piperidyl) sebacate and  
methyl 1,2,2,6,6-pentamethyl-4-piperidyl  
sebacate

#### Dispositions particulières conformément à l'Annexe XVII de REACH et ses amendements successifs:

Aucun

#### 2.3. Autres dangers

Aucune substance PBT, vPvB ou perturbateurs  
endocriniens present en concentration  $\geq 0.1\%$

Aucun autre danger

---

### RUBRIQUE 3 – Composition/informations sur les composants

#### 3.1. Substances

N.A.

#### 3.2. Mélanges

Identification du mélange: FASSAFILL EPOXY COMP.A

#### Composants dangereux aux termes du Règlement CLP et classification relative :

Quantité	Dénomination	N° identification	Classification	Numéro d'enregistrement:
$\geq 15 - < 20$ %	bis-[4-(2,3- époxypropoxy)phényl]propane	CAS:1675-54-3 EC:216-823-5 Index:603-073- 00-2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411  Limites de concentration spécifiques: 5% $\leq$ C < 100%: Skin Irrit. 2 H315 5% $\leq$ C < 100%: Eye Irrit. 2 H319	01-2119456619-26-xxxx
$\geq 3 - < 5$ %	Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	EC:701-263-0	Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411	01-2119454392-40-xxxx
$\geq 1 - < 2.5$ %	oxirane, dérivés mono[(C12-14- alkyloxy) méthyle]	CAS:68609-97-2 EC:271-846-8 Index:603-103- 00-4	Skin Irrit. 2, H315; Skin Sens. 1, H317	01-2119485289-22-xxxx
$\geq 0.1 -$ $< 0.3$ %	Reaction mass of bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	CAS:1065336- 91-5 EC:915-687-0	Skin Sens. 1A, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Repr. 2, H361f, M- Chronic:1, M-Acute:1	01-2119491304-40-xxxx
$< 0.00015$ %	pyrithione zincique	CAS:13463-41-7 EC:236-671-3 Index:613-333- 00-7	Acute Tox. 2, H330 Acute Tox. 3, H301 Eye Dam. 1, H318 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Repr. 1B, H360D, M-Chronic:10, M- Acute:1000  Estimation de la toxicité aiguë, ETA: ETA - Orale: 221mg/kg pc ETA - Inhalation (Poussières/brouillard): 0.14mg/l	

---

### RUBRIQUE 4 – Premiers secours

#### 4.1. Description des mesures de premiers secours

En cas de contact avec la peau :

Enlever immédiatement les vêtements contaminés et les éliminer de manière sûre.

Laver immédiatement avec beaucoup d'eau et éventuellement du savon les parties du corps ayant été en contact avec le produit, même en cas de doute.

Laver entièrement le corps (douche ou bain).

En cas de contact avec les yeux :

En cas de contact avec les yeux, les rincer à l'eau pendant un intervalle de temps adéquat et en tenant les paupières ouvertes, puis consulter immédiatement un ophtalmologue.

Protéger l'œil indemne.

En cas d'ingestion :

Ne pas faire vomir, consulter un médecin montrant cette fiche signalétique et l'étiquetage de danger.

En cas d'inhalation :

Transporter la victime à l'extérieur et la maintenir au chaud et au repos.

#### **4.2. Principaux symptômes et effets, aigus et différés**

Les symptômes et effets résultant inhérents aux risques sont ceux présentés dans la section 2.

#### **4.3. Indication des éventuels soins médicaux immédiats et traitements particuliers nécessaires**

En cas d'incident ou de malaise, consulter immédiatement un médecin (lui montrer, si possible, les instructions pour l'utilisation ou la fiche de sécurité).

---

### **RUBRIQUE 5 – Mesures de lutte contre l'incendie**

#### **5.1. Moyens d'extinction**

Moyens d'extinction appropriés :

CO<sub>2</sub>, extincteurs à poudres, mousse, pulvérisation d'eau.

Moyens d'extinction qui ne doivent pas être utilisés pour des raisons de sécurité :

Jet d'eau.

#### **5.2. Dangers particuliers résultant de la substance ou du mélange**

La combustion produit de la fumée lourde.

Ne pas inhaler les gaz produits par l'explosion et/ou pour la combustion (monoxyde de carbone, dioxyde de carbone, oxydes d'azote).

#### **5.3. Conseils aux pompiers**

Utiliser des appareils respiratoires adaptés.

Recueillir séparément l'eau contaminée utilisée pour éteindre l'incendie. Ne pas la déverser dans le réseau des eaux usées.

Si cela est faisable d'un point de vue de la sécurité, déplacer de la zone de danger immédiat les conteneurs non endommagés.

---

### **RUBRIQUE 6 – Mesures à prendre en cas de dispersion accidentelle**

#### **6.1. Précautions individuelles, équipement de protection et procédures d'urgence**

Porter les dispositifs de protection individuelle.

Emmener les personnes en lieu sûr.

Consulter les mesures de protection exposées aux points 7 et 8.

#### **6.2. Précautions pour la protection de l'environnement**

Empêcher la pénétration dans le sol/sous-sol. Empêcher l'écoulement dans les eaux superficielles ou dans le réseau des eaux usées.

En cas de fuite de gaz ou de pénétration dans les cours d'eau, le sol ou le système d'évacuation d'eau, informer les autorités responsables.

#### **6.3. Méthodes et matériel de confinement et de nettoyage**

Matériel adapté à la collecte: matériel absorbant inerte (sable, vermiculite par ex.)

Après avoir collecté le produit, laver la zone et les matériaux contaminés avec de l'eau.

Retenir l'eau de lavage contaminée et l'éliminer.

#### **6.4. Référence à d'autres rubriques**

Voir également les paragraphes 8 et 13.

---

### **RUBRIQUE 7 – Manipulation et stockage**

#### **7.1. Précautions à prendre pour une manipulation sans danger**

Éviter le contact avec la peau et les yeux, l'inhalation de vapeurs et brouillards.

Ne pas utiliser de conteneurs vides avant qu'ils n'aient été nettoyés.

Avant les opérations de transfert, s'assurer que les conteneurs ne contiennent pas de matériaux incompatibles résiduels.

Conseils d'ordre général en matière d'hygiène du travail:

Les vêtements contaminés doivent être remplacés avant d'accéder aux zones de repas.

Ne pas manger et ne pas boire pendant le travail.

Voir également le paragraphe 8 pour les dispositifs de protection recommandés.

#### **7.2. Conditions d'un stockage sûr, y compris les éventuelles incompatibilités**

Tenir loin de la nourriture, des boissons et aliments pour animaux.

Matières incompatibles:

Voir alinéa 10.5

Indication pour les locaux:

Locaux correctement aérés.

### 7.3. Utilisation(s) finale(s) particulière(s)

Recommandations

Voir alinéa 1.2

Solutions spécifiques pour le secteur industriel

Aucune utilisation particulière

---

## RUBRIQUE 8 – Contrôles de l'exposition/protection individuelle

### 8.1. Paramètres de contrôle

#### Liste des composants contenus dans la formule avec une valeur PNEC

	Limite PNEC	Voie d'exposition	Fréquence d'exposition	Remarques
bis-[4-(2,3-époxypropoxy)phényl] propane CAS: 1675-54-3	0.006 mg/l	Eau douce		
	0.001 mg/l	Eau marine		
	0.341 mg/kg	Sédiments d'eau douce		
	0.034 mg/kg	Sédiments d'eau marine		
	0.065 mg/kg	Sol (agricole)		
	10 mg/l	Micro-organismes dans les traitements des eaux usées (STP)		
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	0.003 mg/l	Eau douce		
	0.3 µg/l	Eau marine		
	10 mg/l	Micro-organismes dans les traitements des eaux usées (STP)		
	0.029 mg/kg	Sédiments d'eau marine		
	0.294 mg/kg	Sédiments d'eau douce		
	0.237 mg/kg	sol		
oxirane, dérivés mono[(C12-14-alkyloxy)méthyle] CAS: 68609-97-2	0.106 mg/l	Eau douce		
	0.011 mg/l	Eau marine		
	10 mg/l	Micro-organismes dans les traitements des eaux usées (STP)		
	30.72 mg/kg	Sédiments d'eau marine		
	307.16 mg/kg	Sédiments d'eau douce		

1.234 sol  
mg/kg

Reaction mass of  
bis(1,2,2,6,6-  
pentamethyl-4-piperidyl)  
sebacate and methyl  
1,2,2,6,6-pentamethyl-4-  
piperidyl sebacate  
CAS: 1065336-91-5

2.2 µg/l Eau douce

1 mg/l Micro-  
organismes dans  
les traitements  
des eaux usées  
(STP)

0.11 Sédiments d'eau  
mg/kg marine

1.05 Sédiments d'eau  
mg/kg douce

0.21 Sol (agricole)  
mg/kg

#### Niveau dérivé sans effet. (DNEL)

	Travail indus riel	Travail profess ionnel	Conso mmate ur	Voie d' exposition	Fréquence d'exposition	Remarques
bis-[4-(2,3- époxypropoxy) phényl]propane CAS: 1675-54-3		0.75 mg/kg	0.089 mg/kg	Cutanée humaine	Long terme, effets systémiques	
		4.93 mg/m3	0.87 mg/m3	Inhalation humaine	Long terme, effets systémiques	
			0.5 mg/kg	Orale humaine	Court terme, effets systémiques	
Formaldehyde, oligomeric reaction products with 1- chloro-2,3- epoxypropane and phenol		104.15 mg/kg	62.5 mg/kg	Cutanée humaine	Long terme, effets systémiques	
		0.008 mg/cm2		Cutanée humaine	Court terme, effets locaux	
		29.39 mg/m3	8.7 mg/m3	Inhalation humaine	Long terme, effets systémiques	
			6.25 mg/kg	Orale humaine	Long terme, effets systémiques	
oxirane, dérivés mono[(C12-14- alkyloxy) méthyle] CAS: 68609-97-2		3.6 mg/m3	0.87 mg/m3	Inhalation humaine	Long terme, effets systémiques	
		1 mg/kg	0.5 mg/kg	Cutanée humaine	Long terme, effets systémiques	
			0.5 mg/kg	Orale humaine	Long terme, effets systémiques	
Reaction mass of bis(1,2,2,6,6- pentamethyl-4- piperidyl) sebacate and methyl 1,2,2,6,6- pentamethyl-4- piperidyl sebacate		1.8 mg/kg	0.9 mg/kg	Cutanée humaine	Long terme, effets systémiques	

1.27 mg/m <sup>3</sup>	0.31 mg/m <sup>3</sup>	Inhalation humaine	Long terme, effets systémiques
	0.18 mg/kg	Orale humaine	Long terme, effets systémiques

## 8.2. Contrôles de l'exposition

Veiller à une ventilation adéquate. Lorsque c'est raisonnablement possible, il est recommandé d'utiliser une ventilation par aspiration localisée et une extraction générale efficace.

Protection des yeux:

Lunettes avec protection latérale (EN 166).

Protection de la peau:

Utilisez des vêtements appropriés pour une protection complète de la peau en fonction de l'activité et de l'exposition (EN 14605/EN 13982), par exemple. combinaison de travail, tablier, chaussures de sécurité, vêtements appropriés.

Protection des mains:

Il n'existe pas de gant, quelque soit sa (ou ses) composition(s), qui donne une résistance illimitée à tout produit chimique (qu'il soit pur ou en mélange).

En cas de contacts prolongés ou répétés, utiliser gants résistant aux produits chimiques.

Matériaux appropriés pour les gants de protection (EN 374/EN 16523); NBR (Caoutchouc nitrile): épaisseur  $\geq 0.4$  mm; temps de perméation  $\geq 480$  min.; FKM (Caoutchouc fluoré): épaisseur  $\geq 0.4$  mm; temps de perméation  $\geq 480$  min.

Le choix de gants adaptés ne dépend pas uniquement du matériau mais également d'autres caractéristiques de qualité variables d'un producteur à un autre, ainsi que des modalités et des temps d'utilisation du mélange.

Protection respiratoire:

Lorsque les travailleurs sont exposés à des concentrations supérieures aux limites d'exposition, ils doivent porter des appareils de protection respiratoire appropriés et homologués.

Dispositif de filtrage combiné (EN 14387).

Contrôles de l'exposition environnementale :

Voir alinéa 6.2

Mesures d'hygiène et techniques

Voir le paragraphe 7.

## RUBRIQUE 9 — Propriétés physiques et chimiques

### 9.1. Informations sur les propriétés physiques et chimiques essentielles

Aspect: liquide pâteux

Couleur : divers

Odeur: caractéristique

Seuil d'odeur : N.D.

Point de fusion/congélation: N.D.

Point d'ébullition initial et intervalle d'ébullition: N.D.

Inflammabilité: pas inflammable

Limite supérieure/inférieure d'inflammabilité ou d'explosion : N.D.

Point d'éclair:  $> 93^{\circ}\text{C}$  ( Évaluation interne )

Température d'auto-inflammation: N.D.

Température de décomposition: N.D.

pH: N.A. ( Non applicable en raison de la nature du produit )

Viscosité cinématique:  $> 20.5$  mm<sup>2</sup>/s (40 °C)

Densité:  $1.66 \pm 0.02$  kg/l ( Méthode interne )

Densité des vapeurs: N.D.

Pression de vapeur: N.D.

Hydrosolubilité: Insoluble

Solubilité dans l'huile: Aucune donnée disponible

Coefficient de partage (n-octanol/eau): N.A.

#### Caractéristiques des particules:

Ce produit contient des nanomatériaux sous forme sphéroïdale et amorphe avec un traitement/recouvrement de surface.

### 9.2. Autres informations

Conductivité: N.D.

Propriétés explosives: N.D.

Propriétés comburantes: N.D.

Taux d'évaporation: N.A.

## RUBRIQUE 10 — Stabilité et réactivité

### 10.1. Réactivité

Stable en conditions normales

## 10.2. Stabilité chimique

Le produit peut générer des phases liquides au fil du temps.

## 10.3. Possibilité de réactions dangereuses

Peut s'enflammer au contact d'agents d'oxydation forts.

Sous l'effet de la chaleur ou en cas d'incendie, des oxydes de Carbone et des vapeurs nuisibles pour la santé peuvent se dégager.

## 10.4. Conditions à éviter

Eviter d'approcher le produit à sources de chaleur.

## 10.5. Matières incompatibles

Agents d'oxydation forts, de réducteurs forts, amines aliphatiques et aromatiques.

Voir alinéa 10.3

## 10.6. Produits de décomposition dangereux

Aucun produit de décomposition dangereux à condition de respecter les prescriptions de stockage et de manipulation.

Voir alinéa 5.2

---

## RUBRIQUE 11 – Informations toxicologiques

### 11.1. Informations sur les classes de danger telles que définies dans le règlement (CE) no 1272/2008

Les résines époxydes contenues dans ce produit sont irritantes mais seulement de manière faible. Toutes les résines époxydes, de toute façon, peuvent causer une sensibilisation de la peau qui varie d'un individu à l'autre.

Dans une personne la dermatite allergique pourrait ne pas se manifester au début mais seulement après plusieurs jours ou semaines de contacts fréquents et prolongés.

C'est pour cette raison, bien que les résines soient faiblement irritantes, que le contact avec la peau doit être soigneusement évité. A la suite de la sensibilisation, mêmes des exposition à de petites quantités de matériel peuvent causer localement oedème et érythème.

#### Informations toxicologiques sur le produit :

a) toxicité aiguë	Non classé	Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
b) corrosion cutanée/irritation cutanée	Le produit est classé: Skin Irrit. 2(H315)	
c) lésions oculaires graves/irritation oculaire	Le produit est classé: Eye Irrit. 2(H319)	
d) sensibilisation respiratoire ou cutanée	Le produit est classé: Skin Sens. 1(H317)	
e) mutagénicité sur les cellules germinales	Non classé	Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
f) cancérogénicité	Non classé	Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
g) toxicité pour la reproduction	Non classé	Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
h) toxicité spécifique pour certains organes cibles — exposition unique	Non classé	Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
i) toxicité spécifique pour certains organes cibles – exposition répétée	Non classé	Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
j) danger par aspiration	Non classé	Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

#### Informations toxicologiques sur les substances principales se trouvant dans le produit :

bis-[4-(2,3-époxypropoxy)phényl]propane a) toxicité aiguë LD50 Orale Rat > 2000 mg/kg

LD50 Peau Rat > 2000 mg/kg

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol a) toxicité aiguë LD50 Peau Rat > 2000 mg/kg

LD50 Orale Rat > 5000 mg/kg

oxirane, dérivés  
mono[(C12-14-alkyloxy)  
méthyle]

a) toxicité aiguë

LC0 Inhalation de vapeurs Rat > 0.15 mg/l 7h

LD50 Orale Rat > 2000 mg/kg

LD50 Peau Lapin > 4000 mg/kg

Reaction mass of  
bis(1,2,2,6,6-  
pentamethyl-4-piperidyl)  
sebacate and methyl  
1,2,2,6,6-pentamethyl-4-  
piperidyl sebacate

a) toxicité aiguë

LD50 Orale Rat > 3230 mg/kg

pyrithione zincique

a) toxicité aiguë

ETA - Orale : 221 mg/kg pc

ETA - Inhalation (Poussières/brouillard) : 0.14  
mg/l

## 11.2. Informations sur les autres dangers

### Propriétés perturbantes le système endocrinien:

Aucun perturbateur endocrinien present en concentration >= 0.1%

## RUBRIQUE 12 – Informations écologiques

Utiliser le produit rationnellement en évitant de le disperser dans la nature.

### 12.1. Toxicité

Informations écotoxicologiques:

Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

#### Liste des propriétés éco-toxicologiques du produit

Le produit est classé: Aquatic Chronic 3(H412)

#### Liste des composants écotoxicologiques

Composant	N° identification	Informations écotoxicologiques
bis-[4-(2,3- époxypropoxy)phényl]propane	CAS: 1675-54-3 - EINECS: 216- 823-5 - INDEX: 603-073-00-2	a) Toxicité aquatique aiguë : EC50 Daphnie 1.8 mg/l 48h  a) Toxicité aquatique aiguë : LC50 Poissons 2 mg/l 96h a) Toxicité aquatique aiguë : EC50 Algues 11 mg/l 72h b) Toxicité aquatique chronique : NOEC Daphnie 0.3 mg/l 21d
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	EINECS: 701- 263-0	a) Toxicité aquatique aiguë : LC50 Poissons 2.54 mg/l 96h  a) Toxicité aquatique aiguë : EC50 Algues 1.8 mg/l 72h a) Toxicité aquatique aiguë : EC50 Daphnie 2.55 mg/l 48h b) Toxicité aquatique chronique : NOEC Daphnie 0.3 mg/l 21d
oxirane, dérivés mono[(C12-14- alkyloxy) méthyle]	CAS: 68609-97- 2 - EINECS: 271-846-8 - INDEX: 603- 103-00-4	a) Toxicité aquatique aiguë : LL50 Poissons > 100 mg/l 96h  a) Toxicité aquatique aiguë : EL50 Daphnie 7.2 mg/l 48h a) Toxicité aquatique aiguë : IC50 Algues 843.75 mg/l 72h
Reaction mass of bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	CAS: 1065336- 91-5 - EINECS: 915-687-0	a) Toxicité aquatique aiguë : LC50 Poissons 0.9 mg/l 96h  a) Toxicité aquatique aiguë : NOEC Algues 0.22 mg/l 72h b) Toxicité aquatique chronique : NOEC Daphnie 6.3 mg/l 21d





IMDG-Groupe d'emballage: N/A

#### **14.5. Dangers pour l'environnement**

Polluant marin: Non

Polluant environnemental: Non

IMDG-EMS: N/A

#### **14.6. Précautions particulières à prendre par l'utilisateur**

Route et Rail (ADR-RID) :

ADR-Etiquette: N/A

ADR - Numéro d'identification du danger : N/A

ADR-Dispositions particulières: N/A

ADR-Code de restriction en tunnel:

Air (IATA) :

IATA-Avion de passagers: N/A

IATA-Avion CARGO: N/A

IATA-Etiquette: N/A

IATA-Danger subsidiaire: N/A

IATA-Erg: N/A

IATA-Dispositions particulières: N/A

Mer (IMDG) :

IMDG-Code de rangement: N/A

IMDG-Note de rangement: N/A

IMDG-Danger subsidiaire: N/A

IMDG-Dispositions particulières: N/A

#### **14.7. Transport maritime en vrac conformément aux instruments de l'OMI**

N.A.

---

### **RUBRIQUE 15 – Informations relatives à la réglementation**

#### **15.1. Réglementations/législation particulières à la substance ou au mélange en matière de sécurité, de santé et d'environnement**

Dir. 98/24/CE (Risques dérivant d'agents chimiques pendant le travail)

Dir. 2000/39/CE (Limites d'exposition professionnelle)

Directive 2010/75/UE

Règlement (CE) n° 1907/2006 (REACH)

Règlement (CE) n° 1272/2008 (CLP)

Règlement (CE) n° 790/2009 (ATP 1 CLP) et (EU) n° 758/2013

Règlement (EU) n° 2020/878

Règlement (EU) n° 286/2011 (ATP 2 CLP)

Règlement (EU) n° 618/2012 (ATP 3 CLP)

Règlement (EU) n° 487/2013 (ATP 4 CLP)

Règlement (EU) n° 944/2013 (ATP 5 CLP)

Règlement (EU) n° 605/2014 (ATP 6 CLP)

Règlement (EU) n° 2015/1221 (ATP 7 CLP)

Règlement (EU) n° 2016/918 (ATP 8 CLP)

Règlement (EU) n° 2016/1179 (ATP 9 CLP)

Règlement (EU) n° 2017/776 (ATP 10 CLP)

Règlement (EU) n° 2018/669 (ATP 11 CLP)

Règlement (EU) n° 2018/1480 (ATP 13 CLP)

Règlement (EU) n° 2019/521 (ATP 12 CLP)

Règlement (EU) n° 2020/217 (ATP 14 CLP)

Règlement (EU) n° 2020/1182 (ATP 15 CLP)

Règlement (EU) n° 2021/643 (ATP 16 CLP)

Règlement (EU) n° 2021/849 (ATP 17 CLP)

Règlement (EU) n° 2022/692 (ATP 18 CLP)

#### **Restrictions liées au produit ou aux substances contenues conformément à l'Annexe XVII de la Réglementation (CE) 1907/2006 (REACH) et ses modifications successives:**

Restrictions liées au produit: Aucun

Restrictions liées aux substances contenues: 30, 40, 75

#### **Dispositions relatives aux directive EU 2012/18 (Seveso III):**

Aucune

#### **Règlement (UE) No 649/2012 (règlement PIC)**

Aucune substance listée

## Classe allemande de danger pour l'eau.

Classe 2: polluant.

## Substances SVHC:

Sur la base des données disponibles, le produit ne contient pas de substances SVHC en pourcentage  $\geq 0.1\%$ .

## 15.2. Évaluation de la sécurité chimique

Aucune évaluation de la sécurité chimique n'a été effectuée pour le mélange

## RUBRIQUE 16 — Autres informations

Code	Description
H315	Provoque une irritation cutanée.
H317	Peut provoquer une allergie cutanée.
H319	Provoque une sévère irritation des yeux.
H361f	Susceptible de nuire à la fertilité.
H400	Très toxique pour les organismes aquatiques.
H410	Très toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H411	Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H412	Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Code	Classe de danger et catégorie de danger	Description
3.2/2	Skin Irrit. 2	Irritation cutanée, Catégorie 2
3.3/2	Eye Irrit. 2	Irritation oculaire, Catégorie 2
3.4.2/1	Skin Sens. 1	Sensibilisation cutanée, Catégorie 1
3.4.2/1A	Skin Sens. 1A	Sensibilisation cutanée, Catégorie 1A
3.7/2	Repr. 2	Toxicité pour la reproduction, Catégorie 2
4.1/A1	Aquatic Acute 1	Danger aigu pour le milieu aquatique, Catégorie 1
4.1/C1	Aquatic Chronic 1	Danger chronique (à long terme) pour le milieu aquatique, Catégorie 1
4.1/C2	Aquatic Chronic 2	Danger chronique (à long terme) pour le milieu aquatique, Catégorie 2
4.1/C3	Aquatic Chronic 3	Danger chronique (à long terme) pour le milieu aquatique, Catégorie 3

## Classification et procédure utilisées pour établir la classification des mélanges conformément au règlement (CE) 1272/2008 [CLP]:

Classification conformément au règlement (CE) n° 1272/2008	Méthode de classification
3.2/2	Méthode de calcul
3.3/2	Méthode de calcul
3.4.2/1	Méthode de calcul
4.1/C3	Méthode de calcul

Ce document a été préparé par une personne compétente qui a été formée de façon appropriée.

Principales sources bibliographiques:

ECDIN - Réseau d'information et Informations chimiques sur l'environnement - Centre de recherche commun, Commission de la Communauté Européenne

PROPRIÉTÉS DANGEREUSES DES MATÉRIAUX INDUSTRIELS DE SAX - Huitième Edition - Van Nostrand Reinold

Fiches de sécurité des fournisseurs de matières premières.

Les informations contenues se basent sur nos connaissances à la date reportée ci-dessus. Elles se réfèrent uniquement au produit indiqué et ne constituent pas de garantie d'une qualité particulière.

L'utilisateur doit s'assurer de la conformité et du caractère complet de ces informations par rapport à l'utilisation spécifique qu'il doit en faire.

Cette fiche annule et remplace toute édition précédente.

Légende des abréviations et acronymes utilisés dans les fiches de données de sécurité

ACGIH: Conférence américaine des hygiénistes industriels gouvernementaux

ADR: Accord européen relatif au transport international des marchandises dangereuses par route.

ATE: Estimation de la toxicité aiguë, ETA

ATEmix: Estimation de la toxicité aiguë (Mélanges)

BEI: Indice Biologique d'Exposition

CAS: Service des résumés analytiques de chimie (division de la Société Chimique Américaine).

CAV: Centre Anti-Poison

CE: Communauté Européenne

CLP: Classification, Etiquetage, Emballage.

CMR: Cancérogènes, Mutagènes et Reprotoxiques

COV: Composés Organiques volatils

CSA: Evaluation de la Sécurité Chimique.  
CSR: Rapport sur la Sécurité Chimique  
DNEL: Niveau dérivé sans effet.  
EC50: Concentration à la moitié de l'efficacité maximale  
ECHA: Agence européenne des produits chimiques  
EINECS: Inventaire européen des substances chimiques commerciales existantes.  
ES: Scénario d'Exposition  
GefStoffVO: Ordonnance sur les substances dangereuses, Allemagne.  
GHS: Système général harmonisé de classification et d'étiquetage des produits chimiques.  
IARC: Centre international de recherche sur le cancer  
IATA: Association internationale du transport aérien.  
IC50: concentration à la moitié de l'inhibition maximale  
IMDG: Code maritime international des marchandises dangereuses.  
LC50: Concentration létale pour 50 pour cent de la population testée.  
LD50: Dose létale pour 50 pour cent de la population testée.  
LDLo: Dose Létale Faible  
N.A.: Non Applicable  
N/A: Non Applicable  
N/D: Non défini / Pas disponible  
N.D.: Pas disponible  
NIOSH: Institut National de la Santé et de la Sécurité professionnelle  
NOAEL: Dose Sans Effet Nocif Observé  
OSHA: Service de la Sécurité et de l'Hygiène du Travail  
PBT: Très persistant, bioaccumulable et toxique  
PGK: Instruction d'emballage  
PNEC: Concentration prévue sans effets.  
PSG: Passagers  
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses.  
STEL: Limite d'exposition à court terme.  
STOT: Toxicité spécifique pour certains organes cibles.  
TLV: Valeur de seuil limite.  
TLV-TWA: Valeur de seuil limite pour une moyenne d'exposition pondérée de 8 heures par jour. (Standard ACGIH)  
vPvB: Très persistant, Très Bioaccumulable.  
WGK: Classe allemande de danger pour l'eau.

**Paragraphes modifiés de la révision précédente:**

- RUBRIQUE 1 — Identification de la substance/du mélange et de la société/de l'entreprise
- RUBRIQUE 2 — Identification des dangers
- RUBRIQUE 3 — Composition/informations sur les composants
- RUBRIQUE 8 — Contrôles de l'exposition/protection individuelle
- RUBRIQUE 9 — Propriétés physiques et chimiques
- RUBRIQUE 11 — Informations toxicologiques
- RUBRIQUE 12 — Informations écologiques
- RUBRIQUE 13 — Considérations relatives à l'élimination
- RUBRIQUE 14 — Informations relatives au transport
- RUBRIQUE 15 — Informations relatives à la réglementation

# Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

## Substance identification

Chemical Name: Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

CAS number: 1065336-91-5

EC number: 915-687-0

Registration Number: 01-2119491304-40-XXXX

Date - Version: 04/04/2022

## INDUSTRIAL USE PRODUCT CATEGORIES (PC1, PC9a, PC32) SECTORS OF USE (SU15, SU17)

### 1. TITLE SECTION

#### EXPOSURE SCENARIO NAME

Industrial use of HALS in articles

#### USE DESCRIPTORS

Product Categories:

Adhesives, Sealants (PC1) Coatings and Paints, Thinners, paint removers (PC9a) Polymer Preparations and Compounds (PC32)

Sectors of use:

Manufacture of fabricated metal products, except machinery and equipment (SU 15). General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment (SU 17).

#### Environment

1. Industrial use of HALS in articles - ERC5

#### Worker

2. Mixing or blending in batch processes for formulation of preparations and articles - PROC5

3: Calendering operations - PROC6

4: Industrial spraying - PROC7

5: Transfer of chemicals from/to vessels/large containers at non dedicated facilities. - PROC8a

6: Transfer of chemicals from/to vessels/large containers at dedicated facilities - PROC8b

7: Roller or brush application - PROC10

8: Treatment of articles by dipping and pouring - PROC13

9: Low energy manipulation of substances bound in materials and/or articles - PROC21

10: High (mechanical) energy work-up of substances bound in materials and/or articles - PROC24

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1 ENVIRONMENTAL EXPOSURE CONTROL - Industrial use of HALS in articles - (ERC5)

##### Amount used, frequency and duration of use (or from service life)

Daily amount per site: ≤ 0,1 ton/day

Daily amount per site: ≤ 22,5 ton/year

##### Conditions and measures for the biological waste water treatment plant

Municipal sewage treatment plant is assumed.

Assumed domestic sewage treatment plant flow: ≥ 2E3 m<sup>3</sup>/day

##### Conditions and measures related to external treatment of waste (including article waste)

Dispose of waste product or used containers according to local regulations.

##### Other conditions affecting environmental exposure

Receiving surface water flow: ≥ 1.8E4 m<sup>3</sup>/day

## 2.2 WORKERS EXPOSURE CONTROL - Mixing or blending in batch processes for formulation of preparations and articles - (PROC5)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%.

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personal operating under supervision. Ensure regular inspection, cleaning and maintenance of equipment and machines. Clear spills immediately. Ensure daily cleaning of the equipment.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.3 WORKERS EXPOSURE CONTROL - Calendering operations - (PROC6)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%.

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personal operating under supervision. Ensure regular inspection, cleaning and maintenance of equipment and machines. Clear spills immediately. Ensure daily cleaning of the equipment.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.4 WORKERS EXPOSURE CONTROL - Industrial spraying - (PROC7)

### **Product features (article)**

Liquid.

Covers concentrations up to 1%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 1 h/day.

### **Technical and organizational conditions and measures**

Provide enclosing hood with very high effectiveness (such as fume cupboard) or effective ventilation by spray booth according to EN 16985. Ensure effectiveness is at least 95%.

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personal operating under supervision. Ensure regular inspection, cleaning and maintenance of equipment and machines. Clear spills immediately. Ensure daily cleaning of the equipment.

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.5 WORKERS EXPOSURE CONTROL - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities. - (PROC8b)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%.

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personal operating under supervision. Ensure regular inspection, cleaning and maintenance of equipment and machines. Clear spills immediately. Ensure daily cleaning of the equipment.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.6 WORKERS EXPOSURE CONTROL - Transfer of chemicals from/to vessels/ large containers at dedicated facilities - (PROC8b)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide enclosing hood with very high effectiveness (such as fume cupboard) or effective ventilation by spray booth according to EN 16985. Ensure effectiveness is at least 95%.

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personal operating under supervision. Ensure regular inspection, cleaning and maintenance of equipment and machines. Clear spills immediately. Ensure daily cleaning of the equipment.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.7 WORKERS EXPOSURE CONTROL - Roller or brush application - (PROC10)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%.

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personal operating under supervision. Ensure regular inspection, cleaning and maintenance of equipment and machines. Clear spills immediately. Ensure daily cleaning of the equipment.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C



## 2.8 WORKERS EXPOSURE CONTROL - Treatment of articles by dipping and pouring - (PROC13)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide specifically designed and maintained LEV (fixed capturing hood type, on-tool extraction or enclosing hood type). Ensure effectiveness is at least 90%.

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personal operating under supervision. Ensure regular inspection, cleaning and maintenance of equipment and machines. Clear spills immediately. Ensure daily cleaning of the equipment.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.9 WORKERS EXPOSURE CONTROL - Low energy manipulation of substances bound in materials and/or articles - (PROC21)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.10 WORKERS EXPOSURE CONTROL - High (mechanical) energy work-up of substances bound in materials and/or articles - (PROC24)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

### 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

#### 3.1 ENVIRONMENTAL RELEASE AND EXPOSURE - Industrial use of HALS in articles - (ERC5)

Release route	Release rate	Release estimation method
Water	0.01 kg/day	Estimated release factor
Air	0 kg/day	Estimated release factor
Soil	0.01 kg/day	Estimated release factor

Protection goal	Exposure estimate	RCR
Fresh water	3.72E-4 mg/L (EUSES 2.1.2)	0.169
Sediment (freshwater)	0.177 mg/kg dw (EUSES 2.1.2)	0.169
Sea water	3.7E-5 mg/L (EUSES 2.1.2)	0.168
Sediment (marine water)	0.018 mg/kg dw (EUSES 2.1.2)	0.16
Wastewater treatment plant	3.2E-3 mg/L (EUSES 2.1.2)	< 0.01
Farmland	0.013 mg/kg dw (EUSES 2.1.2)	0.063
Man via environment - Inhalation (systemic effects)	2.77E-8 mg/m <sup>3</sup> (EUSES 2.1.2)	< 0.01
Man via environment - Oral	3.24E-5 mg/kg bw/day (EUSES 2.1.2)	< 0.01
Man via environment - combined routes	-	< 0.01

#### 3.2 WORKERS EXPOSURE - Mixing or blending in batch processes for formulation of preparations and articles - (PROC5)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.037 mg/m <sup>3</sup> (TRA Workers 3.0)	0.029
Dermal, systemic, long term	0.548 mg/kg bw/day (TRA Workers 3.0)	0.305
Combined, systemic, long term		0.334

#### 3.3 WORKERS EXPOSURE - Calendering operations - (PROC6)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.037 mg/m <sup>3</sup> (TRA Workers 3.0)	0.029
Dermal, systemic, long term	1.097 mg/kg bw/day (TRA Workers 3.0)	0.61
Combined, systemic, long term		0.638

#### 3.4 WORKERS EXPOSURE - Industrial spraying - (PROC7)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.55 mg/m <sup>3</sup> (TRA Workers 3.0)	0.433
Dermal, systemic, long term	0.857 mg/kg bw/day (TRA Workers 3.0)	0.476
Combined, systemic, long term		0.909

### 3.5 WORKERS EXPOSURE - Transfer of chemicals from/to vessels/large containers at non dedicated facilities. - (PROC8a)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.037 mg/m <sup>3</sup> (TRA Workers 3.0)	0.029
Dermal, systemic, long term	0.548 mg/kg bw/day (TRA Workers 3.0)	0.305
Combined, systemic, long term		0.334

### 3.6 WORKERS EXPOSURE - Transfer of chemicals from/to vessels/large containers at dedicated facilities - (PROC8b)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.018 mg/m <sup>3</sup> (TRA Workers 3.0)	0.014
Dermal, systemic, long term	0.548 mg/kg bw/day (TRA Workers 3.0)	0.305
Combined, systemic, long term		0.319

### 3.7 WORKERS EXPOSURE - Roller or brush application - (PROC10)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.037 mg/m <sup>3</sup> (TRA Workers 3.0)	0.029
Dermal, systemic, long term	1.097 mg/kg bw/day (TRA Workers 3.0)	0.61
Combined, systemic, long term		0.638

### 3.8 WORKERS EXPOSURE - Treatment of articles by dipping and pouring - (PROC13)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.5 mg/m <sup>3</sup> (TRA Workers 3.0)	0.394
Dermal, systemic, long term	1.071 mg/kg bw/day (TRA Workers 3.0)	0.595
Combined, systemic, long term		0.989

### 3.9 WORKERS EXPOSURE - Low energy manipulation of substances bound in materials and/or articles - (PROC21)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.2 mg/m <sup>3</sup> (ECETOC TRA Workers)	0.157
Dermal, systemic, long term	0.1 mg/kg bw/day (ECETOC TRA Workers)	0.056
Combined, systemic, long term		0.213

### 3.10 WORKERS EXPOSURE - High (mechanical) energy work-up of substances bound in materials and/or articles - (PROC24)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.2 mg/m <sup>3</sup> (ECETOC TRA Workers)	0.157
Dermal, systemic, long term	0.1 mg/kg bw/day (ECETOC TRA Workers)	0.056
Combined, systemic, long term		0.213

# USO DIFFUSO DA PARTE DI OPERATORI PROFESSIONALI PRODUCT CATEGORIES (PC1, PC9a, PC32) SECTORS USE (SU15, SU17, SU19)

## 1. TITLE SECTION

### **EXPOSURE SCENARIO NAME**

Wide dispersive outdoor use of HALS resulting in inclusion into a matrix

### **USE DESCRIPTORS**

Product Categories:

Adhesives, Sealants (PC1) Coatings and Paints, Thinners, paint removers (PC 9a), Polymer Preparations and Compounds (PC32)

Sectors of use:

Manufacture of fabricated metal products, except machinery and equipment (SU 15). General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment (SU 17). Building and construction work (SU 19)

### **Environment**

1. Wide dispersive outdoor use of HALS resulting in inclusion into a matrix - ERC8f
2. Wide dispersive indoor use of HALS resulting in inclusion into a matrix - ERC8c

### **Worker**

3. Mixing or blending in batch processes for formulation of preparations and articles - PROC5
4. Transfer of chemicals from/to vessels/large containers at non dedicated facilities - PROC8a
5. Transfer of chemicals from/to vessels/large containers at dedicated facilities - PROC8b
6. Roller or brush application - PROC10
7. Non-industrial spraying - PROC13
8. Low energy manipulation of substances bound in materials and/or articles - PROC21
9. High (mechanical) energy work-up of substances bound in materials and/or articles - PROC24

## 2. CONDITIONS OF USE AFFECTING EXPOSURE

### **2.1 ENVIRONMENTAL EXPOSURE CONTROL - Wide dispersive outdoor use of HALS resulting in inclusion into a matrix - (ERC8f)**

#### ***Conditions and measures for the biological waste water treatment plant***

Municipal sewage treatment plant is assumed.

#### ***Conditions and measures related to external treatment of waste (including article waste)***

Dispose of waste product or used containers according to local regulations.

### **2.2 ENVIRONMENTAL EXPOSURE CONTROL - Wide dispersive indoor use of HALS resulting in inclusion into a matrix - (ERC8c)**

#### ***Conditions and measures for the biological waste water treatment plant***

Municipal sewage treatment plant is assumed.

#### ***Conditions and measures related to external treatment of waste (including article waste)***

Dispose of waste product or used containers according to local regulations.

## 2.3 WORKERS EXPOSURE CONTROL - Mixing or blending in batch processes for formulation of preparations and articles - (PROC5)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.4 WORKERS EXPOSURE CONTROL - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities - (PROC8a)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.5 WORKERS EXPOSURE CONTROL - Transfer of chemicals from/to vessels/ large containers at dedicated facilities - (PROC8b)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.6 WORKERS EXPOSURE CONTROL - Roller or brush application - (PROC10)

### **Product features (article)**

Liquid.

Covers concentrations up to 1%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide specifically designed and maintained LEV (receiving hood type). Ensure effectiveness is at least 80%.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear chemically resistant gloves (tested to EN374) in combination with basic employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.7 WORKERS EXPOSURE CONTROL - Non-industrial spraying - (PROC11)

### **Product features (article)**

Liquid.

Covers concentrations up to 1%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Technical and organizational conditions and measures**

Provide specifically designed and maintained LEV (receiving hood type). Ensure effectiveness is at least 80%.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear chemically resistant gloves (tested to EN374) in combination with basic employee training.; If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.8 WORKERS EXPOSURE CONTROL - Low energy manipulation of substances bound in materials and/or articles - (PROC21)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 2.9 WORKERS EXPOSURE CONTROL - High (mechanical) energy work-up of substances bound in materials and/or articles - (PROC24)

### **Product features (article)**

Liquid.

Covers concentrations up to 5%.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Covers use up to 8 h/day

### **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. If skin contamination is expected to extend to other parts of the body, then these body parts should also be protected with impervious garments in a manner equivalent to those described for the hands. For further specifications, refer to section 8 of the SDS.

### **Other conditions affecting worker exposure**

Indoor use.

Assumes process temperature up to 40 °C

## 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

### 3.1 ENVIRONMENTAL RELEASE AND EXPOSURE - Wide dispersive outdoor use of HALS resulting in inclusion into a matrix - (ERC8f)

Release route	Release rate	Release estimation method
Water	0.05 kg/day	ERC
Air	0.15 kg/day	ERC
Soil	5E-3 kg/day	ERC

Protection goal	Exposure estimate	RCR
Fresh water	1.64E-3 mg/L (EUSES 2.1.2)	0.746
Sediment (freshwater)	0.782 mg/kg dw (EUSES 2.1.2)	0.745
Sea water	1.64E-4 mg/L (EUSES 2.1.2)	0.745
Sediment (marine water)	0.078 mg/kg dw (EUSES 2.1.2)	0.71
Wastewater treatment plant	0.016 mg/L (EUSES 2.1.2)	0.016
Farmland	0.064 mg/kg dw (EUSES 2.1.2)	0.307
Man via environment - Inhalation (systemic effects)	2.79E-8 mg/m <sup>3</sup> (EUSES 2.1.2)	< 0.01
Man via environment - Oral	1.82E-4 mg/kg bw/day (EUSES 2.1.2)	< 0.01
Man via environment - combined routes	-	< 0.01



### 3.2 ENVIRONMENTAL RELEASE AND EXPOSURE - Wide dispersive indoor use of HALS resulting in inclusion into a matrix - (ERC8c)

Release route	Release rate	Release estimation method
Water	0.014 kg/day	ERC
Air	6.75E-3 kg/day	ERC
Soil	0 kg/day	ERC

Protection goal	Exposure estimate	RCR
Fresh water	4.83E-4 mg/L (EUSES 2.1.2)	0.22
Sediment (freshwater)	0.23 mg/kg dw (EUSES 2.1.2)	0.219
Sea water	4.81E-5 mg/L (EUSES 2.1.2)	0.219
Sediment (marine water)	0.023 mg/kg dw (EUSES 2.1.2)	0.208
Wastewater treatment plant	4.32E-3 mg/L (EUSES 2.1.2)	< 0.01
Farmland	0.018 mg/kg dw (EUSES 2.1.2)	0.084
Man via environment - Inhalation (systemic effects)	2.77E-8 mg/m <sup>3</sup> (EUSES 2.1.2)	< 0.01
Man via environment - Oral	5.24E-5 mg/kg bw/day (EUSES 2.1.2)	< 0.01
Man via environment - combined routes	-	< 0.01

### 3.3 WORKERS EXPOSURE - Mixing or blending in batch processes for formulation of preparations and articles - (PROC5)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.367 mg/m <sup>3</sup> (TRA Workers 3.0)	0.289
Dermal, systemic, long term	0.548 mg/kg bw/day (TRA Workers 3.0)	0.305
Combined, systemic, long term		0.593

### 3.4 WORKERS EXPOSURE - Transfer of chemicals from/to vessels/large containers at non dedicated facilities - (PROC8a)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.367 mg/m <sup>3</sup> (TRA Workers 3.0)	0.289
Dermal, systemic, long term	0.548 mg/kg bw/day (TRA Workers 3.0)	0.305
Combined, systemic, long term		0.593

### 3.5 WORKERS EXPOSURE - Transfer of chemicals from/to vessels/large containers at dedicated facilities - (PROC8b)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.367 mg/m <sup>3</sup> (TRA Workers 3.0)	0.289
Dermal, systemic, long term	0.548 mg/kg bw/day (TRA Workers 3.0)	0.305
Combined, systemic, long term		0.593



### 3.6 WORKERS EXPOSURE - Roller or brush application - (PROC10)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.97 mg/m <sup>3</sup> (TRA)	0.764
Dermal, systemic, long term	0.274 mg/kg bw/day (TRA Workers 3.0)	0.152
Combined, systemic, long term		0.916

### 3.7 WORKERS EXPOSURE - Non-industrial spraying - (PROC11)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.5 mg/m <sup>3</sup> (TRA)	0.394
Dermal, systemic, long term	1.071 mg/kg bw/day (TRA Workers 3.0)	0.595
Combined, systemic, long term		0.989

### 3.8 WORKERS EXPOSURE - Low energy manipulation of substances bound in materials and/or articles - (PROC21)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.2 mg/m <sup>3</sup> (ECETOC TRA Workers)	0.157
Dermal, systemic, long term	0.1 mg/kg bw/day (ECETOC TRA Workers)	0.056
Combined, systemic, long term		0.213

### 3.9 WORKERS EXPOSURE - High (mechanical) energy work-up of substances bound in materials and/or articles - (PROC24)

Route of exposure and type of effects	Estimated exposure	RCR
Inhalation, systemic, long term	0.6 mg/m <sup>3</sup> (ECETOC TRA Workers)	0.472
Dermal, systemic, long term	0.1 mg/kg bw/day (ECETOC TRA Workers)	0.056
Combined, systemic, long term		0.528

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

# bis-[4-(2,3-epoxipropoxi)phenyl]propane

## Substance identification

Chemical Name: bis-[4-(2,3-epoxipropoxi)phenyl]propane

CAS number: 1675-54-3

Date - Version: 29/12/2021 - 1.3

## INDUSTRIAL USE - PROFESSIONAL USES: PUBLIC SECTOR (ADMINISTRATION, EDUCATION, ENTERTAINMENT, SERVICES, CRAFTS) (SU22).

### 1. TITLE SECTION

**Exposure scenario name:** Industrial use.

**Structured short title:** Professional uses: public sector (administration, education, entertainment, service, crafts) (SU22).

**Substance:** 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC number: 216-823-5

Registration number: 01-2119456619-26

### ENVIRONMENT

**SC 1:** Use of non-reactive processing aid at industrial site (no inclusion in article) ERC4

### WORKER

**SC 2:** Use as laboratory reagents PROC15

**SC 3:** Treatment of articles by dipping and pouring PROC13

**SC 4:** Tableting, compression, extrusion, pelletising, granulation PROC14

**SC 5:** General greasing/lubrication in high energy conditions PROC18

**SC 6:** Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8a

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. ENVIRONMENTAL EXPOSURE CONTROL: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

##### **Product features (article)**

Physical form of the product: Liquid

##### **Amount used (or contained in articles), frequency and duration of use/exposure**

Daily amount per site: 0,6 ton/day

Annual amount per site: 20 ton/year

##### **Conditions and measures related to sewage treatment plant**

STP Type: Municipal wastewater treatment plant.

Learn more about STP: biological elimination.

STP sludge treatment: It may be landfilled when allowed by local regulations.

STP effluent: 2,000 m<sup>3</sup>/day

##### **Other conditions affecting environmental exposure**

Water flow on the receiving surface: 18,000 m<sup>3</sup>/day

Outdoor / Indoor Indoor use.

#### 2.2. WORKERS EXPOSURE CONTROL: Use as laboratory reagents (PROC15)

##### **Product features (article)**

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Temperature: < 40°C

### ***Amount used (or contained in articles), frequency and duration of use/exposure***

Duration: Covers daily exposures up to 8 hours.

### ***Organizational and technical measures and conditions***

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

### ***Conditions and measures for personal protection, hygiene and health assessment***

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

### ***Other conditions affecting worker exposure***

Outdoor / Indoor Inside.

Temperature: < 40°C

## **2.3. WORKERS EXPOSURE CONTROL: Treatment of articles by dipping and pouring (PROC13)**

### ***Product features (article)***

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: < 70°C

### ***Amount used (or contained in articles), frequency and duration of use/exposure***

Duration: Covers daily exposures up to 8 hours.

### ***Organizational and technical measures and conditions***

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 0%.

### ***Conditions and measures for personal protection, hygiene and health assessment***

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

### ***Other conditions affecting worker exposure***

Outdoor / Indoor Inside.

Temperature: < 40°C

## **2.4. WORKERS EXPOSURE CONTROL: Tableting, compression, extrusion, pelletising, granulation (PROC14)**

### ***Product features (article)***

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Temperature: < 40°C

### ***Amount used (or contained in articles), frequency and duration of use/exposure***

Duration: Covers daily exposures up to 8 hours.

### ***Organizational and technical measures and conditions***

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

### **Other conditions affecting worker exposure**

Outdoor / Indoor Inside.

Temperature: < 40°C

## **2.5. WORKERS EXPOSURE CONTROL: General greasing/lubrication in high energy conditions (PROC18)**

### **Product features (article)**

Covers concentrations up to 20%.

Physical form of the product: Liquid.

Temperature: ≤ 800°C

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Duration: Covers daily exposures up to 8 hours.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

### **Other conditions affecting worker exposure**

Outdoor / Indoor Outside.

Industrial or professional environments: Professional use.

Temperature: ≤ 800°C

## **2.6. WORKERS EXPOSURE CONTROL: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC8a)**

### **Product features (article)**

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Duration: Covers daily exposures up to 8 hours.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

### **Other conditions affecting worker exposure**

Outdoor / Indoor Outside.

Industrial or professional environments: Professional use.

Temperature: A process temperature of up to < 40°C is assumed.

### 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

#### 3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Route release	Release rate	Method for estimating for release
water	1.2E-10kg/day	FEICA SPERC 5.1 a.v1
air	3E-4kg/day	FEICA SPERC 5.1 a.v1
Soil	0%	FEICA SPERC 5.1 a.v1

Protection target	Estimated Exposure (EUSES v2.1)	RCR
Fresh water	3.76E-4mg/l	0.063
Fresh water sediments	0.018mg/l	0.053
Sea water	2.95E-5mg/kg dry weight	0.049
Marine sediment	1.42E-3mg/kg dry weight	0.042
Sewage treatment plant	5.68E-11mg/l	< 0.01
Farmland	2.88E-6mg/kg dry weight	< 0.01
Prey for predators (freshwater)	mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	9.13E-4mg/kg wet weight	< 0.01
Main predator prey (marine water)	9.13E-4mg/kg wet weight	< 0.01
Prey for Predators (Terrestrial)	1.68E-4mg/kg wet weight	< 0.01
Man through the environment - inhalation	7.65E-9mg/m <sup>3</sup>	< 0.01
Man through the environment - oral	3E-5mg/kgbw/day	< 0.01
Population exposed through the environment	-	< 0.01

#### 3.2. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.993mg/m <sup>3</sup>	0.201
inhalation	local	Long-term	0.993mg/m <sup>3</sup>	-
inhalation	local	Short term	0.993mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.172mg/kg bw/day	0.045
dermal	local	Short term	9.92E-3mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.247

#### 3.3. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m <sup>3</sup>	0.017
inhalation	local	Long-term	0.085mg/m <sup>3</sup>	-
inhalation	local	Short term	0.085mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.06mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.566

### 3.4. Worker exposure: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.993mg/m <sup>3</sup>	0.201
inhalation	local	Long-term	0.993mg/m <sup>3</sup>	-
inhalation	local	Short term	0.993mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.172mg/kg bw/day	0.229
dermal	local	Short term	0.0025mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.43

### 3.5. Worker exposure: General greasing/lubrication in high energy conditions (PROC18)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.596mg/m <sup>3</sup>	0.121
inhalation	local	Long-term	0.596mg/m <sup>3</sup>	-
inhalation	local	Short term	0.596mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.669

### 3.6. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.596mg/m <sup>3</sup>	0.121
inhalation	local	Long-term	0.596mg/m <sup>3</sup>	-
inhalation	local	Short term	0.596mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.669

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in Section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

## PROFESSIONAL USE - PROFESSIONAL USES: PUBLIC SECTOR (ADMINISTRATION, EDUCATION, ENTERTAINMENT, SERVICES, CRAFTS) (SU22).

### 1. TITLE SECTION

**Exposure scenario name:** Professional.

**Structured short title:** Professional uses: public sector (administration, education, entertainment, service, crafts) (SU22).

**Substance:** 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC number: 216-823-5

Registration number: 01-2119456619-26

### ENVIRONMENT

**SC 1:** Use at an industrial site leading to inclusion in article ERC5

### WORKER

**SC 2:** Industrial spraying PROC7

**SC 3** Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8a

**SC 4:** Transfer of substance or mixture (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC8b

**SC 5:** Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC9

**SC 6:** Application with rollers or brushes PROC10

**SC 7:** Non-industrial spraying PROC11

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. ENVIRONMENTAL EXPOSURE CONTROL: Use at an industrial site leading to inclusion in article (ERC5)

##### **Product features (article)**

Covers a percentage of substance in the product up to 100%.

Physical form of the product: Liquid

##### **Amount used (or contained in articles), frequency and duration of use/exposure**

Annual amount per site: 30,000 tons/year

Daily amount per site: 100 tons/day

##### **Conditions and measures related to sewage treatment plant**

STP Type: Municipal wastewater treatment plant.

Learn more about STP: biological elimination.

STP sludge treatment: It may be landfilled when allowed by local regulations.

STP effluent: 2,000 m<sup>3</sup>/day

##### **Other conditions affecting environmental exposure**

Water flow on the receiving surface: 18,000 m<sup>3</sup>/day

#### 2.2. WORKERS EXPOSURE CONTROL: Industrial spraying (PROC7)

##### **Product features (article)**

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

##### **Amount used (or contained in articles), frequency and duration of use/exposure**

Duration: Covers daily exposures up to 8 hours.

##### **Organizational and technical measures and conditions**

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).



### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

Wear suitable respirator.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 90%.

### **Other conditions affecting worker exposure**

Outdoor / Indoor Inside.

Industrial or professional environments Professional use.

Temperature: Process temperature up to 70°C is assumed.

## **2.3. WORKERS EXPOSURE CONTROL: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC8a)**

### **Product features (article)**

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: 70°C

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Duration: Covers daily exposures up to 8 hours.

### **Organizational and technical measures and conditions**

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 0%.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

### **Other conditions affecting worker exposure**

Outdoor / Indoor Inside.

Industrial or professional environments Professional use.

Temperature: 70°C

## **2.4. WORKERS EXPOSURE CONTROL: Transfer of substance or mixture (charging/discharging) from/to vessels/large containers at dedicated facilities. (PROC8b)**

### **Product features (article)**

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: 70°C

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Duration: Covers daily exposures up to 8 hours.

### **Organizational and technical measures and conditions**

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.



### **Other conditions affecting worker exposure**

Outdoor / Indoor Inside.  
Temperature: 70°C

## **2.5. WORKERS EXPOSURE CONTROL: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)**

### **Product features (article)**

Covers concentrations up to 100%.  
Physical form of the product: Liquid.  
Vapour pressure: 0,00741 Pa  
Temperature: < 50°C

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Duration: Covers daily exposures up to 8 hours.

### **Organizational and technical measures and conditions**

Assumes a good basic standard of occupational hygiene is implemented.  
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).  
Dermal: minimum efficiency of 0%.  
Inhalation: minimum yield of 30%.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.  
Use adequate eye protection.  
Dermal: minimum efficiency of 95%.  
Inhalation: minimum yield of 0%.  
Wear suitable respirator.  
Inhalation: minimum yield of 90%.

### **Other conditions affecting worker exposure**

Outdoor / Indoor Inside.  
Temperature: < 50°C

## **2.6. WORKERS EXPOSURE CONTROL: Application with rollers or brushes (PROC10)**

### **Product features (article)**

Covers the percentage of substance in the product up to 25%.  
Physical form of the product: Liquid.  
Vapour pressure: 0,00741 Pa  
Temperature: < 70°C

### **Amount used (or contained in articles), frequency and duration of use/exposure**

Duration: Covers daily exposures up to 8 hours.

### **Organizational and technical measures and conditions**

Assumes a good basic standard of occupational hygiene is implemented.  
Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).  
Local exhaust ventilation.  
Dermal: minimum efficiency of 0%.  
Inhalation: minimum yield of 90%.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.  
Use adequate eye protection.  
Dermal: minimum efficiency of 99%.  
Inhalation: minimum yield of 0%.

### **Other conditions affecting worker exposure**

Outdoor / Indoor Inside.  
Temperature: < 70°C.

## 2.7. WORKERS EXPOSURE CONTROL: Non-industrial spraying (PROC11)

### Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Temperature: < 40°C

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

### Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

### Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

Wear suitable respirator.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 90%.

### Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C.

## 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

### 3.1. Environmental release and exposure: Use at an industrial site leading to inclusion in article (ERC5)

Route release	Release rate	Method for estimating for release
water	0.06 kg/day	FEICA SPERC 8c.1 b.v1
air	0 kg/day	FEICA SPERC 8c.1 b.v1
Soil	0%	FEICA SPERC 8c.1 b.v1

Protection target	Estimated Exposure (EUSES v2.1)	RCR
Fresh water	3.22E-3mg/l	0,536
Fresh water sediments	0.155mg/l	0,454
Sea water	3.14E-4mg/l	0,523
Marine sediment	0.015mg/kg dry weight	0,442
Sewage treatment plant	0.028mg/l	< 0.01
Farmland	0.05mg/kg dry weight	0,779
Prey for predators (freshwater)	0.048mg/kg wet weight	< 0.01
Prey for predators (marine water)	4.53E-3mg/kg wet weight	< 0.01
Main predator prey (marine water)	1.64E-3mg/kg wet weight	< 0.01
Prey for Predators (Terrestrial)	0.056mg/kg wet weight	< 0.01
Man through the environment - inhalation	Concentration in air: 3.45E-11 mg/m <sup>3</sup>	< 0.01
Man through the environment - oral	1.47E-3mg/kg pc/giorno	< 0.01
Population exposed through the environment	-	< 0.01

### 3.2. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.34mg/m <sup>3</sup> (ART v1.5)	0.069
inhalation	local	Long-term	0.34mg/m <sup>3</sup> (ART v1.5)	-
inhalation	local	Short term	0.78mg/m <sup>3</sup> (ART v1.5)	-
dermal	systemic	Long-term	0.257mg/kgbw/day (ECETOC TRA worker v3)	0.343
dermal	local	Short term	0.012mg/cm <sup>2</sup> (ECETOC TRA worker v3)	-
combined routes	-	-	-	0.412

### 3.3. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.851mg/m <sup>3</sup>	0.173
inhalation	local	Long-term	0.851mg/m <sup>3</sup>	-
inhalation	local	Short term	0.851mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.721

### 3.4. Worker exposure: Transfer of a substance or a mixture (fill/discharge) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m <sup>3</sup>	0.017
inhalation	local	Long-term	0.085mg/m <sup>3</sup>	-
inhalation	local	Short term	0.0851mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.566

### 3.5. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.099mg/m <sup>3</sup>	0.02
inhalation	local	Long-term	0.099mg/m <sup>3</sup>	-
inhalation	local	Short term	0.993mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.343mg/kgbw/day	0.457
dermal	local	Short term	0.05mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.659

### 3.6. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m <sup>3</sup>	0.017
inhalation	local	Long-term	0.085mg/m <sup>3</sup>	-
inhalation	local	Short term	0.085mg/m <sup>3</sup>	-
dermal	systemic	Long-term	0.165mg/kgbw/day	0.219
dermal	local	Short term	0.012mg/cm <sup>2</sup>	-
combined routes	-	-	-	0.237

### 3.7. Worker exposure: Non-industrial spraying (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.34mg/m <sup>3</sup> (ART v1 .5)	0.069
inhalation	local	Long-term	0.34mg/m <sup>3</sup> (ART v1 .5)	-
inhalation	local	Short term	0.78mg/m <sup>3</sup> (ART v1 .5)	-
dermal	systemic	Long-term	0.643mg/kgbw/day (ECETOC TRA worker v3)	0.857
dermal	local	Short term	0.03mg/cm <sup>2</sup> (ECETOC TRA worker v3)	-
combined routes	-	-	-	0.926

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in Section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

**Fiche de Données de Sécurité****FASSAFILL EPOXY COMP.B**

Fiche signalétique du 27/09/2023 révision 2

**RUBRIQUE 1 – Identification de la substance/du mélange et de la société/de l'entreprise****1.1. Identificateur de produit**

Identification du mélange:

Dénomination commerciale: FASSAFILL EPOXY COMP.B

Code commercial: 1281.B

UFI: HRWQ-7RWA-4140-AGT0

**1.2. Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées**

Usage recommandé : Durcisseur pour résines époxy

Usages déconseillés : Non destiné à l'usage des consommateurs; Pour l'usage professionnel seulement

**1.3. Renseignements concernant le fournisseur de la fiche de données de sécurité**

Fournisseur: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Responsable : laboratorio.spresiano@fassabortolo.it

**1.4. Numéro d'appel d'urgence**

ORFILA (INRS): + 33 ( 0 ) 1 45 42 59 59

**RUBRIQUE 2 – Identification des dangers****2.1. Classification de la substance ou du mélange****Règlement (CE) n° 1272/2008 (CLP)**

Skin Corr. 1B Provoque de graves brûlures de la peau et de graves lésions des yeux.

Eye Dam. 1 Provoque de graves lésions des yeux.

Skin Sens. 1 Peut provoquer une allergie cutanée.

Aquatic Chronic 2 Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Effets physico-chimiques nocifs sur la santé humaine et l'environnement :

Aucun autre danger

**2.2. Éléments d'étiquetage****Règlement (CE) n° 1272/2008 (CLP)****Pictogrammes de danger et mention d'avertissement**

Danger

**Mentions de danger**

H314 Provoque de graves brûlures de la peau et de graves lésions des yeux.

H317 Peut provoquer une allergie cutanée.

H411 Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

**Conseils de prudence**

P260 Ne pas respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols.

P273 Éviter le rejet dans l'environnement.

P280 Porter des gants de protection/des vêtements de protection et un équipement de protection des yeux/du visage.

P303+P361+P353 EN CAS DE CONTACT AVEC LA PEAU (ou les cheveux): Enlever immédiatement tous les vêtements contaminés. Rincer la peau à l'eau ou se doucher.

P305+P351+P338 EN CAS DE CONTACT AVEC LES YEUX: Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer.

P310 Appeler immédiatement un CENTRE ANTIPOISON/un médecin.

**Contient:**

3-aminométhyl-3,5,5-triméthylcyclohexylamine

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Propylidynetrimethanol, propoxylated, reaction products with ammonia

N,N-diméthyl-1,3-diaminopropane

Amines, polyethylenepoly-, triethylenetetramine fraction

**Dispositions particulières conformément à l'Annexe XVII de REACH et ses amendements successifs:**

Aucun

**2.3. Autres dangers**

Aucune substance PBT, vPvB ou perturbateurs endocriniens present en concentration  $\geq 0.1\%$

Aucun autre danger

**RUBRIQUE 3 – Composition/informations sur les composants****3.1. Substances**

N.A.

**3.2. Mélanges**

Identification du mélange: FASSAFILL EPOXY COMP.B

**Composants dangereux aux termes du Règlement CLP et classification relative :**

Quantité	Dénomination	N° identification	Classification	Numéro d'enregistrement:
$\geq 50$ - $< 60$ %	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS:68082-29-1 EC:500-191-5	Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317; Aquatic Chronic 2, H411	01-2119972320-44-xxxx
$\geq 15$ - $< 20$ %	Propylidynetrimethanol, propoxylated, reaction products with ammonia	CAS:39423-51-3 EC:500-105-6	Acute Tox. 4, H312; Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Corr. 1B, H314	01-2119556886-20-xxxx
$\geq 12.5$ - $< 15$ %	3-aminométhyl-3,5,5-triméthylcyclohexylamine	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317  Limites de concentration spécifiques: C $\geq 0.001\%$ : Skin Sens. 1A H317  Estimation de la toxicité aiguë, ETA: ETA - Orale: 1030mg/kg pc	01-2119514687-32-xxxx
$\geq 1$ - $< 2.5$ %	N,N-diméthyl-1,3-diaminopropane	CAS:109-55-7 EC:203-680-9	Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1B, H317; Skin Corr. 1B, H314; Eye Dam. 1, H318; STOT SE 3, H335	01-2119486842-27-xxxx
$\geq 0.3$ - $< 0.5$ %	Amines, polyethylenepoly-, triethylenetetramine fraction	CAS:90640-67-8 EC:292-588-2	Acute Tox. 4, H312; Acute Tox. 4, H302; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Chronic 3, H412	01-2119487919-13-xxxx

**RUBRIQUE 4 – Premiers secours****4.1. Description des mesures de premiers secours**

En cas de contact avec la peau :

Enlever immédiatement les vêtements contaminés et les éliminer de manière sûre.

Laver immédiatement avec beaucoup d'eau et éventuellement du savon les parties du corps ayant été en contact avec le produit,

même en cas de doute.

CONSULTER IMMEDIATEMENT UN MEDECIN.

En cas de contact avec les yeux :

En cas de contact avec les yeux, les rincer à l'eau pendant un intervalle de temps adéquat et en tenant les paupières ouvertes, puis consulter immédiatement un ophtalmologue.

Protéger l'œil indemne.

En cas d'ingestion :

Ne pas faire vomir, consulter un médecin montrant cette fiche signalétique et l'étiquetage de danger.

En cas d'inhalation :

Transporter la victime à l'extérieur et la maintenir au chaud et au repos.

#### **4.2. Principaux symptômes et effets, aigus et différés**

Les symptômes et effets résultant inhérents aux risques sont ceux présentés dans la section 2.

#### **4.3. Indication des éventuels soins médicaux immédiats et traitements particuliers nécessaires**

En cas d'incident ou de malaise, consulter immédiatement un médecin (lui montrer, si possible, les instructions pour l'utilisation ou la fiche de sécurité).

---

### **RUBRIQUE 5 – Mesures de lutte contre l'incendie**

#### **5.1. Moyens d'extinction**

Moyens d'extinction appropriés :

CO2, extincteurs à poudres, mousse, pulvérisation d'eau.

Moyens d'extinction qui ne doivent pas être utilisés pour des raisons de sécurité :

Jet d'eau.

#### **5.2. Dangers particuliers résultant de la substance ou du mélange**

La combustion produit de la fumée lourde.

Ne pas inhaler les gaz produits par l'explosion et/ou pour la combustion (monoxyde de carbone, dioxyde de carbone, oxydes d'azote).

#### **5.3. Conseils aux pompiers**

Utiliser des appareils respiratoires adaptés.

Recueillir séparément l'eau contaminée utilisée pour éteindre l'incendie. Ne pas la déverser dans le réseau des eaux usées.

Si cela est faisable d'un point de vue de la sécurité, déplacer de la zone de danger immédiat les conteneurs non endommagés.

---

### **RUBRIQUE 6 – Mesures à prendre en cas de dispersion accidentelle**

#### **6.1. Précautions individuelles, équipement de protection et procédures d'urgence**

Porter les dispositifs de protection individuelle.

Emmener les personnes en lieu sûr.

Consulter les mesures de protection exposées aux points 7 et 8.

#### **6.2. Précautions pour la protection de l'environnement**

Empêcher la pénétration dans le sol/sous-sol. Empêcher l'écoulement dans les eaux superficielles ou dans le réseau des eaux usées.

En cas de fuite de gaz ou de pénétration dans les cours d'eau, le sol ou le système d'évacuation d'eau, informer les autorités responsables.

#### **6.3. Méthodes et matériel de confinement et de nettoyage**

Matériel adapté à la collecte: matériel absorbant inerte (sable, vermiculite par ex.)

Après avoir collecté le produit, laver la zone et les matériaux contaminés avec de l'eau.

Retenir l'eau de lavage contaminée et l'éliminer.

#### **6.4. Référence à d'autres rubriques**

Voir également les paragraphes 8 et 13.

---

### **RUBRIQUE 7 – Manipulation et stockage**

#### **7.1. Précautions à prendre pour une manipulation sans danger**

Éviter le contact avec la peau et les yeux, l'inhalation de vapeurs et brouillards.

Ne pas utiliser de conteneurs vides avant qu'ils n'aient été nettoyés.

Avant les opérations de transfert, s'assurer que les conteneurs ne contiennent pas de matériaux incompatibles résiduels.

Conseils d'ordre général en matière d'hygiène du travail:

Les vêtements contaminés doivent être remplacés avant d'accéder aux zones de repas.

Ne pas manger et ne pas boire pendant le travail.

Voir également le paragraphe 8 pour les dispositifs de protection recommandés.

#### **7.2. Conditions d'un stockage sûr, y compris les éventuelles incompatibilités**

Tenir loin de la nourriture, des boissons et aliments pour animaux.

Matières incompatibles:

Voir alinéa 10.5

Indication pour les locaux:

Locaux correctement aérés.

### 7.3. Utilisation(s) finale(s) particulière(s)

Recommandations

Voir alinéa 1.2

Solutions spécifiques pour le secteur industriel

Aucune utilisation particulière

---

## RUBRIQUE 8 – Contrôles de l'exposition/protection individuelle

### 8.1. Paramètres de contrôle

#### Liste des composants contenus dans la formule avec une valeur PNEC

	Limite PNEC	Voie d'exposition	Fréquence d'exposition	Remarques
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1	0 mg/l	Eau marine		
	0.004 mg/l	Eau douce		
	3.84 mg/l	Micro-organismes dans les traitements des eaux usées (STP)		
	43.4 mg/kg	Sédiments d'eau marine		
	434.02 mg/kg	Sédiments d'eau douce		
Propylidynetrimehtanol, propoxylated, reaction products with ammonia CAS: 39423-51-3	86.78 mg/kg	sol		
	0.004 mg/l	Eau douce		
	0.0004 mg/l	Eau marine		
	0.022 mg/kg	Sédiments d'eau douce		
	0.002 mg/kg	Sédiments d'eau marine		
3-aminométhyl-3,5,5-triméthylcyclohexylamine CAS: 2855-13-2	10 mg/l	Micro-organismes dans les traitements des eaux usées (STP)		
	0.002 mg/kg	Sol (agricole)		
	0.06 mg/l	Eau douce		
	0.006 mg/l	Eau marine		
	3.18 mg/l	Micro-organismes dans les traitements des eaux usées (STP)		
5.784 mg/kg	Sédiments d'eau douce			



	0.578 mg/kg	Sédiments d'eau marine
	1.121 mg/kg	Sol (agricole)
N,N-diméthyl-1,3-diaminopropane CAS: 109-55-7	0.073 mg/l	Eau douce
	0.007 mg/l	Eau marine
	10 mg/l	Micro-organismes dans les traitements des eaux usées (STP)
	0.735 mg/kg	Sédiments d'eau douce
	0.073 mg/kg	Sédiments d'eau marine
	0.104 mg/kg	Sol (agricole)
Amines, polyethylenepoly-, triethylenetetramine fraction CAS: 90640-67-8	0.027 mg/l	Eau douce
	0.003 mg/l	Eau marine
	0.857 mg/kg	Sédiments d'eau marine
	8.572 mg/kg	Sédiments d'eau douce
	1.25 mg/kg	Sol (agricole)

#### Niveau dérivé sans effet. (DNEL)

	Travailleur industriel	Travailleur professionnel	Consommateur	Voie d'exposition	Fréquence d'exposition	Remarques
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1	3.9 mg/m3	0.97 mg/m3		Inhalation humaine	Long terme, effets systémiques	
	1.1 mg/kg	0.56 mg/kg		Cutanée humaine	Long terme, effets systémiques	
		0.56 mg/kg		Orale humaine	Long terme, effets systémiques	
Propylidynetrimethanol, propoxylated, reaction products with ammonia CAS: 39423-51-3	14.1 mg/m3			Inhalation humaine	Long terme, effets systémiques	
	1.6 mg/kg			Cutanée humaine	Long terme, effets systémiques	
N,N-diméthyl-1,3-diaminopropane CAS: 109-55-7	1.2 mg/m3			Inhalation humaine	Long terme, effets systémiques	

Amines,  
polyéthylène poly-,  
triéthylène tetramine  
fraction  
CAS: 90640-67-8

0.54 mg/m <sup>3</sup>	0.096 mg/m <sup>3</sup>	Inhalation humaine	Long terme, effets systémiques
---------------------------	----------------------------	-----------------------	-----------------------------------

0.14 mg/kg		Orale humaine	Long terme, effets systémiques
---------------	--	------------------	-----------------------------------

## 8.2. Contrôles de l'exposition

Veiller à une ventilation adéquate. Lorsque c'est raisonnablement possible, il est recommandé d'utiliser une ventilation par aspiration localisée et une extraction générale efficace.

Protection des yeux:

Lunettes avec protection latérale (EN 166).

Protection de la peau:

Utilisez des vêtements appropriés pour une protection complète de la peau en fonction de l'activité et de l'exposition (EN 14605/EN 13982), par exemple. combinaison de travail, tablier, chaussures de sécurité, vêtements appropriés.

Protection des mains:

Il n'existe pas de gant, quelque soit sa (ou ses) composition(s), qui donne une résistance illimitée à tout produit chimique (qu'il soit pur ou en mélange).

En cas de contacts prolongés ou répétés, utiliser gants résistant aux produits chimiques.

Matériaux appropriés pour les gants de protection (EN 374/EN 16523); NBR (Caoutchouc nitrile): épaisseur  $\geq 0.4$  mm; temps de perméation  $\geq 480$  min.; FKM (Caoutchouc fluoré): épaisseur  $\geq 0.4$  mm; temps de perméation  $\geq 480$  min.

Le choix de gants adaptés ne dépend pas uniquement du matériau mais également d'autres caractéristiques de qualité variables d'un producteur à un autre, ainsi que des modalités et des temps d'utilisation du mélange.

Protection respiratoire:

Lorsque les travailleurs sont exposés à des concentrations supérieures aux limites d'exposition, ils doivent porter des appareils de protection respiratoire appropriés et homologués.

Dispositif de filtrage combiné (EN 14387).

Contrôles de l'exposition environnementale :

Voir alinéa 6.2

Mesures d'hygiène et techniques

Voir le paragraphe 7.

---

## RUBRIQUE 9 — Propriétés physiques et chimiques

### 9.1. Informations sur les propriétés physiques et chimiques essentielles

Aspect: liquide pâteux

Couleur : translucide

Odeur: légèrement ammoniacal

Seuil d'odeur : N.D.

Point de fusion/congélation: N.D.

Point d'ébullition initial et intervalle d'ébullition: N.D.

Inflammabilité: pas inflammable

Limite supérieure/inférieure d'inflammabilité ou d'explosion : N.D.

Point d'éclair:  $> 93^{\circ}\text{C}$  ( Évaluation interne )

Température d'auto-inflammation: N.D.

Température de décomposition: N.D.

pH:  $\geq 11.30 \leq 11.50$  ( Méthode interne - 20% en dispersion aqueuse )

Viscosité cinématique:  $> 20.5$  mm<sup>2</sup>/s (40 °C)

Densité:  $1.10 \pm 0.02$  kg/l ( Méthode interne )

Densité des vapeurs: N.D.

Pression de vapeur: N.D.

Hydrosolubilité: miscible en tous les rapports

Solubilité dans l'huile: Aucune donnée disponible

Coefficient de partage (n-octanol/eau): N.A.

#### Caractéristiques des particules:

Ce produit contient des nanomatériaux sous forme sphéroïdale et amorphe avec un traitement/recouvrement de surface.

### 9.2. Autres informations

Conductivité: N.D.

Propriétés explosives: N.D.

Propriétés comburantes: N.D.

Taux d'évaporation: N.A.

---

## RUBRIQUE 10 — Stabilité et réactivité

### 10.1. Réactivité

Stable en conditions normales

## 10.2. Stabilité chimique

Le produit peut générer des phases liquides au fil du temps.

## 10.3. Possibilité de réactions dangereuses

Peut s'enflammer au contact d'agents d'oxydation forts.

Peut générer des gaz inflammables et/ou toxiques au contact de métaux élémentaires (alcalis et terres alcalines), d'acides minéraux oxydants, de substances organiques halogénées, de peroxydes et d'hydroperoxydes organiques, d'agents d'oxydation forts, de réducteurs forts.

## 10.4. Conditions à éviter

Eviter d'approcher le produit à sources de chaleur.

## 10.5. Matières incompatibles

Voir alinéa 10.3

## 10.6. Produits de décomposition dangereux

Aucun produit de décomposition dangereux à condition de respecter les prescriptions de stockage et de manipulation.

Voir alinéa 5.2

---

## RUBRIQUE 11 — Informations toxicologiques

### 11.1. Informations sur les classes de danger telles que définies dans le règlement (CE) no 1272/2008

#### Informations toxicologiques sur le produit :

a) toxicité aiguë	Non classé	
		Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
b) corrosion cutanée/irritation cutanée	Le produit est classé: Skin Corr. 1B(H314)	
c) lésions oculaires graves/irritation oculaire	Le produit est classé: Eye Dam. 1(H318)	
d) sensibilisation respiratoire ou cutanée	Le produit est classé: Skin Sens. 1(H317)	
e) mutagénicité sur les cellules germinales	Non classé	
		Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
f) cancérogénicité	Non classé	
		Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
g) toxicité pour la reproduction	Non classé	
		Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
h) toxicité spécifique pour certains organes cibles — exposition unique	Non classé	
		Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
i) toxicité spécifique pour certains organes cibles – exposition répétée	Non classé	
		Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
j) danger par aspiration	Non classé	
		Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

#### Informations toxicologiques sur les substances principales se trouvant dans le produit :

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	a) toxicité aiguë	LD50 Orale Rat > 2000 mg/kg
		LD50 Peau Rat > 2000 mg/kg
Propylidyntrimethanol, propoxylated, reaction products with ammonia	a) toxicité aiguë	LD50 Orale Rat 550 mg/kg
		LD50 Peau Rat > 1000 mg/kg
3-aminométhyl-3,5,5-triméthylcyclohexylamine	a) toxicité aiguë	ETA - Orale : 1030 mg/kg pc

N,N-diméthyl-1,3-diaminopropane	a) toxicité aiguë	LD50 Orale Rat 922 mg/kg LC50 Inhalation Rat > 4.31 mg/l 4h
Amines, polyéthylène-poly-, triéthylène-tétramine fraction	a) toxicité aiguë	LD50 Orale Rat 1716 mg/kg LD50 Peau Lapin 1465 mg/kg

## 11.2. Informations sur les autres dangers

### Propriétés perturbantes le système endocrinien:

Aucun perturbateur endocrinien présent en concentration  $\geq 0.1\%$

## RUBRIQUE 12 – Informations écologiques

Utiliser le produit rationnellement en évitant de le disperser dans la nature.

### 12.1. Toxicité

Informations écotoxicologiques:

Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

#### Liste des propriétés éco-toxicologiques du produit

Le produit est classé: Aquatic Chronic 2(H411)

#### Liste des composants écotoxicologiques

Composant	N° identification	Informations écotoxicologiques
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triéthylène-tétramine	CAS: 68082-29-1 - EINECS: 500-191-5	a) Toxicité aquatique aiguë : LC50 Poissons 7.07 mg/l 96h a) Toxicité aquatique aiguë : EC50 Daphnie 7.07 mg/l 48h a) Toxicité aquatique aiguë : EC50 Algues 4.34 mg/l 72h
Propylidynetriméthanol, propoxylated, reaction products with ammonia	CAS: 39423-51-3 - EINECS: 500-105-6	a) Toxicité aquatique aiguë : LC50 Poissons > 100 mg/l 96h a) Toxicité aquatique aiguë : EC50 Daphnie 13 mg/l 48h a) Toxicité aquatique aiguë : ErC50 Algues 4.4 mg/l 72h b) Toxicité aquatique chronique : NOEC Algues 1 mg/l 72h
3-aminométhyl-3,5,5-triméthylcyclohexylamine	CAS: 2855-13-2 - EINECS: 220-666-8 - INDEX: 612-067-00-9	a) Toxicité aquatique aiguë : LC50 Poissons 110 mg/l 96h a) Toxicité aquatique aiguë : EC50 Daphnie 23 mg/l 48h a) Toxicité aquatique aiguë : EC50 Algues > 50 mg/l 72h
N,N-diméthyl-1,3-diaminopropane	CAS: 109-55-7 - EINECS: 203-680-9	a) Toxicité aquatique aiguë : LC50 Poissons 122 mg/l 96h a) Toxicité aquatique aiguë : EC50 Daphnie 59.5 mg/l 48h a) Toxicité aquatique aiguë : EC50 Algues 53.5 mg/l 72h
Amines, polyéthylène-poly-, triéthylène-tétramine fraction	CAS: 90640-67-8 - EINECS: 292-588-2	a) Toxicité aquatique aiguë : LC50 Poissons 330 mg/l 96h a) Toxicité aquatique aiguë : EC50 Daphnie 31.1 mg/l 48h a) Toxicité aquatique aiguë : EC10 Algues 1.34 mg/l 72h

### 12.2. Persistance et dégradabilité

Composant	Persistance/dégradabilité :
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and	Pas rapidement dégradable

triethylenetetramine

Propylidynetrimethanol,  
propoxylated, reaction products  
with ammonia Pas rapidement dégradable

3-aminométhyl-3,5,5-  
triméthylcyclohexylamine Pas rapidement dégradable

Amines, polyethylenepoly-,  
triethylenetetramine fraction Pas rapidement dégradable

### 12.3. Potentiel de bioaccumulation

N.A.

### 12.4. Mobilité dans le sol

N.A.

### 12.5. Résultats des évaluations PBT et vPvB

Sur la base des données disponibles, le produit ne contient pas de substances PBT/vPvB en pourcentage  $\geq 0.1\%$ .

### 12.6. Propriétés perturbant le système endocrinien

Aucun perturbateur endocrinien présent en concentration  $\geq 0.1\%$

### 12.7. Autres effets néfastes

N.A.

---

## RUBRIQUE 13 – Considérations relatives à l'élimination

### 13.1. Méthodes de traitement des déchets

Récupérer si possible. Envoyer à des usines de traitement autorisées ou à l'incinération dans des conditions contrôlées. Opérer en respectant les dispositions locales et nationales en vigueur.


Ne pas laisser pénétrer dans les égouts ni les cours d'eau.

Les récipients qui ne sont pas vides sont à traiter conformément aux exigences légales nationales ou locales en matière de déchets.

Une fois le produit périmé, il doit être éliminé conformément à la réglementation en vigueur.

---

## RUBRIQUE 14 – Informations relatives au transport



### 14.1. Numéro ONU ou numéro d'identification

1759

### 14.2. Désignation officielle de transport de l'ONU

ADR-Nom d'expédition: SOLIDE CORROSIF, N.S.A. (3-aminométhyl-3,5,5-triméthylcyclohexylamine)

IATA-Nom technique: CORROSIVE SOLID, N.O.S. (3-aminométhyl-3,5,5-triméthylcyclohexylamine)

IMDG-Nom technique: CORROSIVE SOLID, N.O.S. (3-aminométhyl-3,5,5-triméthylcyclohexylamine)

### 14.3. Classe(s) de danger pour le transport

ADR-Classe: 8

IATA-Classe: 8

IMDG-Classe: 8

### 14.4. Groupe d'emballage

ADR-Groupe d'emballage: II

IATA-Groupe d'emballage: II

IMDG-Groupe d'emballage: II

### 14.5. Dangers pour l'environnement

Composant toxique le plus important: Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Polluant marin: Oui

Polluant environnemental: Oui

IMDG-EMS: F-A, S-B

#### 14.6. Précautions particulières à prendre par l'utilisateur

Route et Rail (ADR-RID) :

Exempté d'ADR:

ADR-Etiquette: 8

ADR - Numéro d'identification du danger : 80

ADR-Dispositions particulières: 274

ADR-Code de restriction en tunnel:

Air (IATA) :

IATA-Avion de passagers: 859

IATA-Avion CARGO: 863

IATA-Etiquette: 8

IATA-Danger subsidiaire: -

IATA-Erg: 8L

IATA-Dispositions particulières: A3 A803

Mer (IMDG) :

IMDG-Code de rangement: Category A

IMDG-Note de rangement: -

IMDG-Danger subsidiaire: -

IMDG-Dispositions particulières: 274

#### 14.7. Transport maritime en vrac conformément aux instruments de l'OMI

N.A.

---

### RUBRIQUE 15 – Informations relatives à la réglementation

#### 15.1. Réglementations/législation particulières à la substance ou au mélange en matière de sécurité, de santé et d'environnement

Dir. 98/24/CE (Risques dérivant d'agents chimiques pendant le travail)

Dir. 2000/39/CE (Limites d'exposition professionnelle)

Directive 2010/75/UE

Règlement (CE) n° 1907/2006 (REACH)

Règlement (CE) n° 1272/2008 (CLP)

Règlement (CE) n° 790/2009 (ATP 1 CLP) et (EU) n° 758/2013

Règlement (EU) n° 2020/878

Règlement (EU) n° 286/2011 (ATP 2 CLP)

Règlement (EU) n° 618/2012 (ATP 3 CLP)

Règlement (EU) n° 487/2013 (ATP 4 CLP)

Règlement (EU) n° 944/2013 (ATP 5 CLP)

Règlement (EU) n° 605/2014 (ATP 6 CLP)

Règlement (EU) n° 2015/1221 (ATP 7 CLP)

Règlement (EU) n° 2016/918 (ATP 8 CLP)

Règlement (EU) n° 2016/1179 (ATP 9 CLP)

Règlement (EU) n° 2017/776 (ATP 10 CLP)

Règlement (EU) n° 2018/669 (ATP 11 CLP)

Règlement (EU) n° 2018/1480 (ATP 13 CLP)

Règlement (EU) n° 2019/521 (ATP 12 CLP)

Règlement (EU) n° 2020/217 (ATP 14 CLP)

Règlement (EU) n° 2020/1182 (ATP 15 CLP)

Règlement (EU) n° 2021/643 (ATP 16 CLP)

Règlement (EU) n° 2021/849 (ATP 17 CLP)

Règlement (EU) n° 2022/692 (ATP 18 CLP)

#### Restrictions liées au produit ou aux substances contenues conformément à l'Annexe XVII de la Réglementation (CE) 1907/2006 (REACH) et ses modifications successives:

Restrictions liées au produit: Aucun

Restrictions liées aux substances contenues: 40, 75

#### Dispositions relatives aux directive EU 2012/18 (Seveso III):

**Catégorie Seveso III  
conformément à l'Annexe 1,  
partie 1**

le produit appartient à la  
catégorie: E2

**Exigences relatives au seuil  
bas (tonnes)**

200

**Exigences relatives au seuil  
haut (tonnes)**

500

#### Règlement (UE) No 649/2012 (règlement PIC)

Aucune substance listée

### Classe allemande de danger pour l'eau.

Classe 3: très polluant.

### Substances SVHC:

Sur la base des données disponibles, le produit ne contient pas de substances SVHC en pourcentage  $\geq 0.1\%$ .

### 15.2. Évaluation de la sécurité chimique

Aucune évaluation de la sécurité chimique n'a été effectuée pour le mélange

---

## RUBRIQUE 16 – Autres informations

Code	Description
H226	Liquide et vapeurs inflammables.
H302	Nocif en cas d'ingestion.
H312	Nocif par contact cutané.
H314	Provoque de graves brûlures de la peau et de graves lésions des yeux.
H315	Provoque une irritation cutanée.
H317	Peut provoquer une allergie cutanée.
H318	Provoque de graves lésions des yeux.
H335	Peut irriter les voies respiratoires.
H411	Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H412	Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Code	Classe de danger et catégorie de danger	Description
2.6/3	Flam. Liq. 3	Liquide inflammable, Catégorie 3
3.1/4/Dermal	Acute Tox. 4	Toxicité aiguë (par voie cutanée), Catégorie 4
3.1/4/Oral	Acute Tox. 4	Toxicité aiguë (par voie orale), Catégorie 4
3.2/1B	Skin Corr. 1B	Corrosion cutanée, Catégorie 1B
3.2/2	Skin Irrit. 2	Irritation cutanée, Catégorie 2
3.3/1	Eye Dam. 1	Lésions oculaires graves, Catégorie 1
3.4.2/1	Skin Sens. 1	Sensibilisation cutanée, Catégorie 1
3.4.2/1A	Skin Sens. 1A	Sensibilisation cutanée, Catégorie 1A
3.4.2/1B	Skin Sens. 1B	Sensibilisation cutanée, Catégorie 1B
3.8/3	STOT SE 3	Toxicité spécifique pour certains organes cibles —Exposition unique STOT un., Catégorie 3
4.1/C2	Aquatic Chronic 2	Danger chronique (à long terme) pour le milieu aquatique, Catégorie 2
4.1/C3	Aquatic Chronic 3	Danger chronique (à long terme) pour le milieu aquatique, Catégorie 3

### Classification et procédure utilisées pour établir la classification des mélanges conformément au règlement (CE) 1272/2008 [CLP]:

Classification conformément au règlement (CE) n° 1272/2008	Méthode de classification
3.2/1B	Méthode de calcul
3.3/1	Méthode de calcul
3.4.2/1	Méthode de calcul
4.1/C2	Méthode de calcul

Ce document a été préparé par une personne compétente qui a été formée de façon appropriée.

Principales sources bibliographiques:

ECDIN - Réseau d'information et Informations chimiques sur l'environnement - Centre de recherche commun, Commission de la Communauté Européenne

PROPRIÉTÉS DANGEREUSES DES MATÉRIAUX INDUSTRIELS DE SAX - Huitième Edition - Van Nostrand Reinold

Fiches de sécurité des fournisseurs de matières premières.

Les informations contenues se basent sur nos connaissances à la date reportée ci-dessus. Elles se réfèrent uniquement au produit indiqué et ne constituent pas de garantie d'une qualité particulière.

L'utilisateur doit s'assurer de la conformité et du caractère complet de ces informations par rapport à l'utilisation spécifique qu'il doit en faire.

Cette fiche annule et remplace toute édition précédente.

Légende des abréviations et acronymes utilisés dans les fiches de données de sécurité

ACGIH: Conférence américaine des hygiénistes industriels gouvernementaux

ADR: Accord européen relatif au transport international des marchandises dangereuses par route.

ATE: Estimation de la toxicité aiguë, ETA  
ATEmix: Estimation de la toxicité aiguë (Mélanges)  
BEI: Indice Biologique d'Exposition  
CAS: Service des résumés analytiques de chimie (division de la Société Chimique Américaine).  
CAV: Centre Anti-Poison  
CE: Communauté Européenne  
CLP: Classification, Etiquetage, Emballage.  
CMR: Cancérogènes, Mutagènes et Reprotoxiques  
COV: Composés Organiques volatils  
CSA: Evaluation de la Sécurité Chimique.  
CSR: Rapport sur la Sécurité Chimique  
DNEL: Niveau dérivé sans effet.  
EC50: Concentration à la moitié de l'efficacité maximale  
ECHA: Agence européenne des produits chimiques  
EINECS: Inventaire européen des substances chimiques commerciales existantes.  
ES: Scénario d'Exposition  
GefStoffVO: Ordonnance sur les substances dangereuses, Allemagne.  
GHS: Système général harmonisé de classification et d'étiquetage des produits chimiques.  
IARC: Centre international de recherche sur le cancer  
IATA: Association internationale du transport aérien.  
IC50: concentration à la moitié de l'inhibition maximale  
IMDG: Code maritime international des marchandises dangereuses.  
LC50: Concentration létale pour 50 pour cent de la population testée.  
LD50: Dose létale pour 50 pour cent de la population testée.  
LDLo: Dose Létale Faible  
N.A.: Non Applicable  
N/A: Non Applicable  
N/D: Non défini / Pas disponible  
N.D.: Pas disponible  
NIOSH: Institut National de la Santé et de la Sécurité professionnelle  
NOAEL: Dose Sans Effet Nocif Observé  
OSHA: Service de la Sécurité et de l'Hygiène du Travail  
PBT: Très persistant, bioaccumulable et toxique  
PGK: Instruction d'emballage  
PNEC: Concentration prévue sans effets.  
PSG: Passagers  
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses.  
STEL: Limite d'exposition à court terme.  
STOT: Toxicité spécifique pour certains organes cibles.  
TLV: Valeur de seuil limite.  
TLV-TWA: Valeur de seuil limite pour une moyenne d'exposition pondérée de 8 heures par jour. (Standard ACGIH)  
vPvB: Très persistant, Très Bioaccumulable.  
WGK: Classe allemande de danger pour l'eau.

**Paragraphes modifiés de la révision précédente:**

- RUBRIQUE 1 — Identification de la substance/du mélange et de la société/de l'entreprise
- RUBRIQUE 2 — Identification des dangers
- RUBRIQUE 3 — Composition/informations sur les composants
- RUBRIQUE 8 — Contrôles de l'exposition/protection individuelle
- RUBRIQUE 9 — Propriétés physiques et chimiques
- RUBRIQUE 11 — Informations toxicologiques
- RUBRIQUE 12 — Informations écologiques
- RUBRIQUE 13 — Considérations relatives à l'élimination
- RUBRIQUE 14 — Informations relatives au transport
- RUBRIQUE 15 — Informations relatives à la réglementation



# 3-aminomethyl-3,5,5-trimethylcyclohexylamine

## Substance identification

Chemical Name: 3-aminomethyl-3,5,5-trimethylcyclohexylamine

CAS number: 2855-13-2

EU index number: 612-067-00-9

EINECS number: 220-666-8

## ES1 Formulation or repackaging - INDUSTRIAL USES

### 1. TITLE SECTION

**Exposure scenario name:** Preparation and repackaging of substances and mixtures

**Date - Version:** 15/07/2020 - 1.0

**Life cycle stage:** Formulation or repackaging

**Main user group:** Industrial uses

**Sector(s) of use:** Industrial uses (SU3) - Large-scale production of basic chemicals (including petroleum products) (SU8) - Formulation [blending] of preparations and/or repackaging (SU10)

#### **Contributing scenario - Environment**

**CS1 Wet formulation:** ERC2

#### **Contributing scenario - Worker**

**CS2 Use in closed systems:** PROC3

**CS3 Material Transfers:** PROC8a

**CS4 Material Transfers:** PROC8b

**CS5 Material Transfers:** PROC9

**CS6 Blend Operations:** PROC5

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

**Environmental release categories:** Formulation of mixtures (ERC2)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

#### **Amount used, frequency and duration of use**

**Amounts used:** Annual amount per site 2500 t

**Release Type:** Continuous release

**Issue days:** 300 days/year

**Further environmental conditions:**

Wet formulation

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

#### **Measures and technical-organizational conditions**

**Control measures to prevent releases:**

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

#### **Conditions and measures for the municipal sewage treatment plant**

**Type of sewage treatment plant (STP):** Municipal STP

**STP effluent (m<sup>3</sup>/day):** 8640

#### **Conditions and measures for waste treatment (including the product waste)**

**Waste treatment:** Do not spread industrial sludge on natural soils.

### ***Other operational conditions affecting environmental exposure***

**Local seawater dilution factor:** 100

**Local fresh water dilution factor:** 11

**Flow rate of receiving surface water:** 86400

Indoor use

## **2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)**

**Process categories:** Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

### ***Product features (article)***

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### ***Amount used, frequency and duration of use/exposure***

**Duration:** 480 min

**Frequency:** 5 days/week

### ***Measures and technical-organizational conditions***

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### ***Conditions and measures related to personal protection, hygiene and health verification***

#### **Personal protective equipment:**

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 95 %

### ***Other operational conditions affecting worker exposure***

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand.

***Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.***

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

## **2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)**

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

### ***Product features (article)***

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### ***Amount used, frequency and duration of use/exposure***

**Duration:** 240 min

**Frequency:** 5 days/week

### ***Measures and technical-organizational conditions***

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### ***Conditions and measures related to personal protection, hygiene and health verification***

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

### ***Other operational conditions affecting worker exposure***

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

## 2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 480 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 98 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 97%

**Body parts exposed:** Palm of a hand. Possible skin contact is believed to be limited to the hands.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

## 2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

**Process categories:** Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 480 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 98 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand. Possible skin contact is believed to be limited to the hands.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

## 2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

**Process categories:** Mixing or Blending in Batch Processes (PROC5)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 480 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

## 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

### 3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

### 3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	4,258 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.212

### 3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.706

### 3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	2,129 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.106
by inhalation, systemic, short-term	2,129 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.106

### 3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.353

### 3.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.353

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## ES2 Formulation or repackaging - PROFESSIONAL USES

### 1. TITLE SECTION

**Exposure scenario name:** Preparation and repackaging of substances and mixtures

**Date - Version:** 10/03/2020 - 1.0

**Life cycle stage:** Formulation or repackaging

**Main user group:** Professional uses

**Sector(s) of use:** Manufacture of bulk, large scale chemicals (including petroleum products) (SU8) - Formulation [mixing] of preparations and/or re-packaging (SU10) - Professional uses (SU22)

#### **Contributing scenario - Environment**

**CS1 Wet formulation:** ERC2

#### **Contributing scenario - Worker**

**CS2 Use in closed systems:** PROC3

**CS3 Material Transfers:** PROC8a

**CS3 Material Transfers:** PROC8b

**CS3 Material Transfers:** PROC9

**CS6 Blend Operations:** PROC5

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.2. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

**Environmental release categories:** Formulation of mixtures (ERC2)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

#### **Amount used, frequency and duration of use**

**Amounts used:** Annual amount per site 2500 t

**Release Type:** Continuous release

**Issue days:** 300 days/year

**Further environmental conditions:**

Wet formulation

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

#### **Measures and technical-organizational conditions**

**Control measures to prevent releases:**

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

#### **Conditions and measures for the municipal sewage treatment plant**

**Type of sewage treatment plant (STP):** Municipal STP

**STP effluent (m<sup>3</sup>/day):** 8640

#### **Conditions and measures for waste treatment (including the product waste)**

**Waste treatment:** Do not spread industrial sludge on natural soils.

#### **Other operational conditions affecting environmental exposure**

**Local seawater dilution factor:** 100

**Local fresh water dilution factor:** 11

**Flow rate of receiving surface water:** 86400

Indoor use

## 2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

**Process categories:** Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 480 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 95 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

## 2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 240 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.



## 2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 240 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand. Possible skin contact is believed to be limited to the hands.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

## 2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

**Process categories:** Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 240 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand. Possible skin contact is believed to be limited to the hands.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.



## 2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

**Process categories:** Mixing or Blending in Batch Processes (PROC5)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 1.57 Pa

### **Amount used, frequency and duration of use/exposure**

**Duration:** 60 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

**Technical organizational measures:** For further data, see section 8 of the safety data sheet.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Palm of a hand. Possible skin contact is believed to be limited to the hands.

**Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

## 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

### 3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

### 3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	8,515 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.424

### 3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.353

### 3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.706

### 3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.706

### 3.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.706

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

# Amines, polyethylenepoly-, triethylenetetramine fraction

## Substance identification

Chemical Name: Amines, polyethylenepoly-, triethylenetetramine fraction  
CAS number: 90640-67-8

## INDUSTRIAL APPLICATION OF COATINGS AND PAINTS - INDUSTRIAL USE

### 1. TITLE SECTION

**Exposure scenario name:** Industrial application of coatings and paints

**Date - Version:** 15/07/2020 - 1.0

**Life cycle stage:** Use at industrial sites

**Main user group:** Industrial uses

**Sector(s) of use:** Industrial uses (SU3)

#### **Contributing scenario - Environment**

**CS1 Wet polymerization:** ERC4

#### **Contributing scenario - Worker**

**CS2 Blend Operations:** PROC5

**CS3 Spraying:** PROC7

**CS4 Material Transfers:** PROC8a

**CS5 Material Transfers:** PROC8b

**CS6 Material Transfers:** PROC9

**CS7 Roller and brush application:** PROC10

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC4)

**Environmental release categories:** Use of non-reactive processing aid at industrial site (no inclusion into or onto article). (ERC4)

#### **Product features (article)**

**Physical form of the product:** Liquid

#### **Amount used, frequency and duration of use**

**Amounts used:** Daily quantity per site 2114 kg/day

**Release Type:** Continuous release

**Issue days:** 220 days a year

#### **Measures and technical-organizational conditions**

**Control measures to prevent releases:** No specific measures identified.

#### **Other operational conditions affecting environmental exposure**

**Local fresh water dilution factor:** 1000

## 2.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

**Process categories:** Mixing or Blending in Batch Processes (PROC5)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### **Amount used, frequency and duration of use/exposure**

**Duration:** Includes use up to 60 min.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.3. CS3 Contributing Scenario - Worker: Spray (PROC7)

**Process categories:** Industrial spray application (PROC7)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 15%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 95% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8a)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 25%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.5. CS5 Contributing Scenario - Worker: Material transfers (PROC8b)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 25%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.6 Contributing Scenario CS6 - Worker: Material transfers (PROC9)

**Process categories:** Transfer of a substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 15%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.7 CS7 Contributing Scenario - Worker: Roller and brush application (PROC10)

**Process categories:** Roller and brush application (PROC10)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 15%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Includes use up to 60 min.

**Additional conditions for human health:** Limit the amount of substance in the product to 0.5%

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

#### 3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC4)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.00317 mg/l	EUSES	0.017
fresh water sediment	1.6 mg/kg bw/day	EUSES	0.017
sea water	0.00042 mg/l	EUSES	0.008
Marine sediment	0.212 mg/kg bw/day	EUSES	0.008
ground	0.114 mg/kg bw/day	EUSES	0.006

#### 3.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.68 mg/kg bw/day	N.d.	0.12
by inhalation, systemic, long-term	0.365 mg/m <sup>3</sup>	N.d.	0.366
by inhalation, systemic, short-term	0.731 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.486

#### 3.3. CS3 Contributing Scenario - Worker: Spray (PROC7)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.128 mg/kg bw/day	N.d.	0.226
by inhalation, systemic, long-term	0.457 mg/m <sup>3</sup>	N.d.	0.457
by inhalation, systemic, short-term	0.914 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.683

#### 3.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.041 mg/kg bw/day	N.d.	0.072
by inhalation, systemic, long-term	0.548 mg/m <sup>3</sup>	N.d.	0.548
by inhalation, systemic, short-term	1,097 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.621

### 3.5. CS5 Contributing Scenario - Worker: Material transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.034 mg/kg bw/day	N.d.	0.06
by inhalation, systemic, long-term	0.548 mg/m <sup>3</sup>	N.d.	0.548
by inhalation, systemic, short-term	1.096 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.609

### 3.6. Contributing Scenario CS6 - Worker: Material transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.068 mg/kg bw/day	N.d.	0.12
by inhalation, systemic, long-term	0.365 mg/m <sup>3</sup>	N.d.	0.366
by inhalation, systemic, short-term	1.22 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.706

### 3.7. CS7 Contributing Scenario - Worker: Roller and brush application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.082 mg/kg bw/day	N.d.	0.144
by inhalation, systemic, long-term	0.457 mg/m <sup>3</sup>	N.d.	0.229
by inhalation, systemic, short-term	0.914 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.373

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



# USE IN RIGID FOAM, COATINGS, ADHESIVES AND SEALANTS - INDUSTRIAL USE

## 1. TITLE SECTION

**Exposure scenario name:** Use in rigid foam, coatings, adhesives and sealants

**Date - Version:** 03/18/2020 - 1.0

**Life cycle stage:** Use at industrial sites

**Main user group:** Industrial uses

**Sector(s) of use:** Industrial uses (SU3)

### **Contributing scenario - Environment**

**CS1 Wet polymerization:** ERC4

### **Contributing scenario - Worker**

**CS2 Blend Operations:** PROC5

**CS3 Spraying:** PROC7

**CS4 Material Transfers:** PROC8a

**CS5 Material Transfers:** PROC8b

**CS6 Material Transfers:** PROC9

**CS7 Roller and brush application:** PROC10

## 2. CONDITIONS OF USE AFFECTING EXPOSURE

### 2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC4)

**Environmental release categories:** Use of non-reactive processing aid at industrial site (no inclusion into or onto article). (ERC4)

#### **Product features (article)**

**Physical form of the product:** Liquid

#### **Amount used, frequency and duration of use**

**Amounts used:** Daily quantity per site 2114 kg/day

**Release Type:** Continuous release

**Issue days:** 220 days a year

#### **Measures and technical-organizational conditions**

**Control measures to prevent releases:** No specific measures identified.

#### **Other operational conditions affecting environmental exposure**

**Local fresh water dilution factor:** 1000

### 2.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

**Process categories:** Mixing or Blending in Batch Processes (PROC5)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Includes use up to 60 min.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 2.3. CS3 Contributing Scenario - Worker: Spray (PROC7)

**Process categories:** Industrial spray application (PROC7)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 15%.

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 95% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 2.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8a)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 25%.

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.5. CS5 Contributing Scenario - Worker: Material transfers (PROC8b)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 25%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

### **Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.6. Contributing Scenario CS6 - Worker: Material transfers (PROC9)

**Process categories:** Transfer of a substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 15%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

### **Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.7. CS7 Contributing Scenario - Worker: Roller and brush application (PROC10)

**Process categories:** Roller and brush application (PROC10)

### ***Product features (article)***

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 5%.

### ***Amount used, frequency and duration of use/exposure***

**Duration:** Covers up to 8 hours of daily exposure.

**Additional conditions for human health:** Limit the amount of substance in the product to 0.5%

### ***Measures and technical-organizational conditions***

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### ***Conditions and measures related to personal protection, hygiene and health verification***

**Personal protective equipment:** -Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### ***Other operational conditions affecting worker exposure***

Indoor use

***Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.***

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

#### 3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC4)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.00317 mg/l	EUSES	0.017
fresh water sediment	1.6 mg/kg bw/day	EUSES	0.017
sea water	0.00042 mg/l	EUSES	0.008
Marine sediment	0.212 mg/kg bw/day	EUSES	0.008
ground	0.114 mg/kg bw/day	EUSES	0.006

#### 3.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.68 mg/kg bw/day	N.d.	0.12
by inhalation, systemic, long-term	0.365 mg/m <sup>3</sup>	N.d.	0.366
by inhalation, systemic, short-term	0.731 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.486

#### 3.3. CS3 Contributing Scenario - Worker: Spray (PROC7)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.128 mg/kg bw/day	N.d.	0.226
by inhalation, systemic, long-term	0.457 mg/m <sup>3</sup>	N.d.	0.457
by inhalation, systemic, short-term	0.914 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.683

#### 3.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.041 mg/kg bw/day	N.d.	0.072
by inhalation, systemic, long-term	0.548 mg/m <sup>3</sup>	N.d.	0.548
by inhalation, systemic, short-term	1.097 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.621

### 3.5. CS5 Contributing Scenario - Worker: Material transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.034 mg/kg bw/day	N.d.	0.06
by inhalation, systemic, long-term	0.548 mg/m <sup>3</sup>	N.d.	0.548
by inhalation, systemic, short-term	1.096 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.609

### 3.6. Contributing Scenario CS6 - Worker: Material transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.068 mg/kg bw/day	N.d.	0.12
by inhalation, systemic, long-term	0.365 mg/m <sup>3</sup>	N.d.	0.366
by inhalation, systemic, short-term	1.22mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.706

### 3.7. CS7 Contributing Scenario - Worker: Roller and brush application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.082 mg/kg bw/day	N.d.	0.144
by inhalation, systemic, long-term	0.457 mg/m <sup>3</sup>	N.d.	0.229
by inhalation, systemic, short-term	0.914 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.373

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## - INDUSTRIAL APPLICATION OF COATINGS AND PAINTS - PROFESSIONAL USE

### 1. TITLE SECTION

**Exposure scenario name:** Industrial application of coatings and paints

**Date - Version:** 03/18/2020 - 1.0

**Life cycle stage:** Generalized use by professional operators

**Main user group:** Professional uses

**Sector(s) of use:** Professional uses (SU22)

#### ***Contributing scenario - Environment***

**CS1 Wet polymerization:** ERC8a - ERC8d

#### ***Contributing scenario - Worker***

**CS2 Blend Operations:** PROC5

**CS3 Material Transfers:** PROC8a

**CS4 Material Transfers:** PROC8b

**CS5 Material Transfers:** PROC9

**CS6 Roller and brush application:** PROC10

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC4)

**Environmental release categories:** Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor). (ERC8a, ERC8d)

##### ***Product features (article)***

**Physical form of the product:** Liquid

##### ***Amount used, frequency and duration of use***

**Amounts used:** Daily quantity per site 15500kg/day

**Release Type:** Continuous release

**Issue days:** 300 days/year

##### ***Measures and technical-organizational conditions***

**Control measures to prevent releases:** Preventive treatment of wastewater by neutralization. No other specific measures identified.

##### ***Other operational conditions affecting environmental exposure***

**Local fresh water dilution factor:** 1000

#### 2.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

**Process categories:** Mixing or Blending in Batch Processes (PROC5)

##### ***Product features (article)***

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

##### ***Amount used, frequency and duration of use/exposure***

**Duration:** Includes use up to 60 min.

##### ***Measures and technical-organizational conditions***

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

##### ***Conditions and measures related to personal protection, hygiene and health verification***

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

##### ***Other operational conditions affecting worker exposure***

Indoor use



**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 2.3. CS3 Contributing Scenario - Worker: Material transfers (PROC8a)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Includes use up to 15 min.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Inhalation - minimum 95% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 2.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8b)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 5%.

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.



## 2.5. CS5 Contributing Scenario - Worker: Material transfers (PROC9)

**Process categories:** Transfer of a substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 25%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.6. Contributing Scenario CS6 - Worker: Roller and brush application (PROC10)

**Process categories:** Roller and brush application (PROC10)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 5%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

**Additional conditions for human health:** Limit the amount of substance in the product to 2%

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

#### 3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8a, ERC8d)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.0037 mg/l	EUSES	N.d.
fresh water sediment	1.6 mg/kg bw/day	EUSES	N.d.
sea water	0.00042 mg/l	EUSES	N.d.
Marine sediment	0.212 mg/kg bw/day	EUSES	N.d.
ground	0.114 mg/kg bw/day	EUSES	N.d.

#### 3.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.68 mg/kg bw/day	N.d.	0.12
by inhalation, systemic, long-term	0.365 mg/m <sup>3</sup>	N.d.	0.366
by inhalation, systemic, short-term	0.731 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.486

#### 3.3. CS3 Contributing Scenario - Worker: Material transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.09 mg/kg bw/day	N.d.	0.15
by inhalation, systemic, long-term	0.61 mg/m <sup>3</sup>	N.d.	0.609
by inhalation, systemic, short-term	1.22mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.76

#### 3.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.14 mg/kg bw/day	N.d.	0.248
by inhalation, systemic, long-term	0.76 mg/m <sup>3</sup>	N.d.	0.076
by inhalation, systemic, short-term	1.52 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.324

### 3.5. CS5 Contributing Scenario - Worker: Material transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.14 mg/kg bw/day	N.d.	0.248
by inhalation, systemic, long-term	0.76 mg/m <sup>3</sup>	N.d.	0.076
by inhalation, systemic, short-term	1.52 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.324

### 3.6. Contributing Scenario CS6 - Worker: Roller and brush application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.14 mg/kg bw/day	N.d.	0.248
by inhalation, systemic, long-term	0.76 mg/m <sup>3</sup>	N.d.	0.076
by inhalation, systemic, short-term	0.243 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.498

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

# USE IN RIGID FOAM, COATINGS, ADHESIVES AND SEALANTS - PROFESSIONAL USE

## 1. TITLE SECTION

**Exposure scenario name:** Industrial application of coatings and paints

**Date - Version:** 03/18/2020 - 1.0

**Life cycle stage:** Use in rigid foam, coatings, adhesives and sealants

**Main user group:** Professional uses

**Sector(s) of use:** Professional uses (SU22)

### **Contributing scenario - Environment**

**CS1 Wet polymerization:** ERC8a - ERC8d

### **Contributing scenario - Worker**

**CS2 Blend Operations:** PROC5

**CS3 Material Transfers:** PROC8a

**CS4 Material Transfers:** PROC8b

**CS5 Material Transfers:** PROC9

**CS6 Roller and brush application:** PROC10

## 2. CONDITIONS OF USE AFFECTING EXPOSURE

### 2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC4)

**Environmental release categories:** Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor). (ERC8a, ERC8d)

#### **Product features (article)**

**Physical form of the product:** Liquid

#### **Amount used, frequency and duration of use**

**Amounts used:** Daily quantity per site 15500kg/day

**Release Type:** Continuous release

**Issue days:** 300 days/year

#### **Measures and technical-organizational conditions**

**Control measures to prevent releases:** Preventive treatment of wastewater by neutralization. No other specific measures identified.

#### **Other operational conditions affecting environmental exposure**

**Local fresh water dilution factor:** 1000

### 2.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

**Process categories:** Mixing or Blending in Batch Processes (PROC5)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Includes use up to 60 min.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 2.3. CS3 Contributing Scenario - Worker: Material transfers (PROC8a)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Includes use up to 15 min.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Inhalation - minimum 95% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 2.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8b)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

#### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 0.5 %

#### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

#### **Measures and technical-organizational conditions**

**Technical organizational measures:** No specific measures identified.

#### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

#### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.5. CS5 Contributing Scenario - Worker: Material transfers (PROC9)

**Process categories:** Transfer of a substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 5%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

## 2.6. Contributing Scenario CS6 - Worker: Roller and brush application (PROC10)

**Process categories:** Roller and brush application (PROC10)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** < 500Pa

**Concentration of the substance in the product:** Includes concentrations up to 5%.

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers up to 8 hours of daily exposure.

### **Measures and technical-organizational conditions**

**Technical organizational measures:** Provide supplementary ventilation to points where emissions occur. Inhalation - minimum 90% efficiency.

### **Conditions and measures related to personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable gloves, tested according to EN347. Dermal - minimum 90% efficiency. Wear suitable respiratory protection.

**Additional conditions for human health:** Assumes a good basic standard of occupational hygiene is implemented.

### **Other operational conditions affecting worker exposure**

Indoor use

**Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.**

**Further information on good practices:** Supervise the implementation of risk management measures and compliance with the required operational conditions.

### 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

#### 3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8a, ERC8d)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.0037 mg/l	EUSES	N.d.
fresh water sediment	1.6 mg/kg bw/day	EUSES	N.d.
sea water	0.00042 mg/l	EUSES	N.d.
Marine sediment	0.212 mg/kg bw/day	EUSES	N.d.
ground	0.114 mg/kg bw/day	EUSES	N.d.

#### 3.2. CS2 Contributing Scenario - Worker: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.68 mg/kg bw/day	N.d.	0.12
by inhalation, systemic, long-term	0.365 mg/m <sup>3</sup>	N.d.	0.366
by inhalation, systemic, short-term	0.731 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.486

#### 3.3. CS3 Contributing Scenario - Worker: Material transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.09 mg/kg bw/day	N.d.	0.15
by inhalation, systemic, long-term	0.61 mg/m <sup>3</sup>	N.d.	0.609
by inhalation, systemic, short-term	1.22mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.76

#### 3.4. CS4 Contributing Scenario - Worker: Material transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.14 mg/kg bw/day	N.d.	0.248
by inhalation, systemic, long-term	0.76 mg/m <sup>3</sup>	N.d.	0.076
by inhalation, systemic, short-term	1.52 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.324

### 3.5. CS5 Contributing Scenario - Worker: Material transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.14 mg/kg bw/day	N.d.	0.248
by inhalation, systemic, long-term	0.76 mg/m <sup>3</sup>	N.d.	0.076
by inhalation, systemic, short-term	1.52 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.324

### 3.6. Contributing Scenario CS6 - Worker: Roller and brush application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
skin contact, systemic, long-term	0.14 mg/kg bw/day	N.d.	0.248
by inhalation, systemic, long-term	0.76 mg/m <sup>3</sup>	N.d.	0.076
by inhalation, systemic, short-term	1.52 mg/m <sup>3</sup>	N.d.	<0.001
combined routes, systemic, long-term	N.d.	N.d.	0.373

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



# Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

## Substance identification

Chemical Name: Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine  
CAS number: 68082-29-1

## USE AT INDUSTRIAL USES

### 1. TITLE SECTION

**Exposure scenario name:** Industrial production of varnishes and enamels - Industrial application of coatings and paints - Use in rigid foam, coatings, adhesives and sealants - Use in composite and foundry materials

**Date - Version:** 03/12/2020 - 1.0

**Life cycle stage:** Use at industrial sites

**Main user group:** Industrial uses

**Sector(s) of use:** Industrial uses (SU3)

#### **Contributing scenario - Environment**

**CS1 Wet polymerization:** ERC5

#### **Contributing scenario - Worker**

**CS2 Hardening:** PROC4

**CS3 Spraying - Dermal Exposure Assessment:** PROC7

**CS4 Spraying - Dermal Exposure Assessment:** PROC7

**CS5 Material transfers:** PROC8b

**CS6 Material Transfers:** PROC9

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. CS1 Environment Contributing Scenario: Wet Polymerization (ERC5)

**Environmental release categories:** Industrial use leading to inclusion into/onto an article (ERC5)

#### **Product features (article)**

**Physical form of the product:** Liquid

#### **Amount used, frequency and duration of use**

**Amounts used:** Daily quantity per site 3.33 tons/day - Yearly amount per site 999 tons/year

**Release Type:** Continuous release

**Issue days:** 300 days/year

#### **Conditions and measures for the municipal sewage treatment plant**

**Type of sewage treatment plant (STP):** Municipal STP - Water: minimum efficiency of 91.34%

**STP effluent (m<sup>3</sup>/day):** 2000

#### **Conditions and measures for waste treatment (including the product waste)**

**Waste treatment:** No specific measures identified.

#### **Other operational conditions affecting environmental exposure**

**Flow rate of receiving surface water:** 18000 m<sup>3</sup>/day

## 2.2. Contributing Scenario CS2 - Worker: Curing (PROC4)

**Process categories:** Chemical production where opportunity for exposure arises (PROC4)

### **Product features (article)**

**Physical form of the product:** Liquid

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers a daily exposure up to 8 hours.

### **Measures and technical-organizational conditions**

#### **Technical organizational measures:**

Provide a good standard of general ventilation (up to 3 air changes per hour).

Ensure personnel are trained to minimize exposure.

Dermal - minimum efficiency 90%

Inhalation - minimum efficiency 90%

### **Conditions and measures for personal protection, hygiene and health verification**

#### **Personal protective equipment:**

Wear an appropriate apron to avoid skin exposure.

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency 95%

### **Other operational conditions affecting worker exposure**

Indoor use

**Temperature:** A process temperature of up to 40°C is assumed

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Possible skin contact is believed to be limited to the hands.

## 2.3. Contributing Scenario CS3 - Spraying: Dermal Exposure Assessment (PROC7)

**Process categories:** Industrial spray application (PROC7)

### **Product features (article)**

**Physical form of the product:** Liquid

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers a daily exposure up to 8 hours.

### **Measures and technical-organizational conditions**

#### **Technical organizational measures:**

Provide a good standard of general ventilation (up to 3 air changes per hour).

Ensure personnel are trained to minimize exposure.

Dermal - minimum efficiency 95%

Inhalation - minimum efficiency 90%

### **Conditions and measures for personal protection, hygiene and health verification**

#### **Personal protective equipment:**

Wear an appropriate apron to avoid skin exposure.

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency 95%

### **Other operational conditions affecting worker exposure**

Indoor use

**Temperature:** A process temperature of up to 40°C is assumed

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Possible skin contact is believed to be limited to the hands and forearms.

## 2.4. Contributing Scenario CS4 - Spraying: Inhalation Exposure Assessment (PROC7)

**Process categories:** Industrial spray application (PROC7)

### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 7.9E-08 Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### **Amount used, frequency and duration of use/exposure**

**Duration:** For each application, avoid using for a duration exceeding 480 min.

### **Conditions and measures for personal protection, hygiene and health verification**

**Personal protective equipment:** Wear suitable respiratory protection. Inhalation - minimum efficiency 95%

### **Other operational conditions affecting worker exposure**

Indoor use

**Room size:** Covers use in a room size of 300m<sup>2</sup>.

**Temperature:** Includes use at room temperature.

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Possible skin contact is believed to be limited to the hands and forearms.

**Additional conditions for human health:** Moderate amount used (0.3-3 l/minute)

**Learn more about good practices. The obligations set out in the REACH Regulation in Article 37(4) do not apply.**

**Further information on good practices:** Use a splash guard. For further data, see section 8 of the safety data sheet. Wear suitable respiratory protection.

## 2.5. Contributing Scenario CS5 - Worker: Material Transfers (PROC8b)

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

### **Product features (article)**

**Physical form of the product:** Liquid

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers a daily exposure up to 8 hours.

### **Measures and technical-organizational conditions**

**Technical organizational measures:**

Provide a good standard of general ventilation (up to 3 air changes per hour).

Ensure personnel are trained to minimize exposure.

Dermal - minimum efficiency 95%

Inhalation - minimum efficiency 95%

### **Conditions and measures for personal protection, hygiene and health verification**

**Personal protective equipment:**

Wear an appropriate apron to avoid skin exposure.

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency 95 %

### **Other operational conditions affecting worker exposure**

Indoor use

**Temperature:** A process temperature of up to 40°C is assumed

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Possible skin contact is believed to be limited to the hands and forearms.

## 2.6. Contributing Scenario CS6 - Worker: Material Transfers (PROC9)

**Process categories:** Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

### Product features (article)

**Physical form of the product:** Liquid

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### Amount used, frequency and duration of use/exposure

**Duration:** Covers a daily exposure up to 8 hours.

### Measures and technical-organizational conditions

#### Technical organizational measures:

Provide a good standard of general ventilation (up to 3 air changes per hour).

Ensure personnel are trained to minimize exposure.

Dermal - minimum efficiency 90%

Inhalation - minimum efficiency 90%

### Conditions and measures for personal protection, hygiene and health verification

#### Personal protective equipment:

Wear an appropriate apron to avoid skin exposure.

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency 95 %

### Other operational conditions affecting worker exposure

Indoor use

**Temperature:** A process temperature of up to 40°C is assumed

**Ventilation Rate:** Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

**Body parts exposed:** Possible skin contact is believed to be limited to the hands.

## 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

### 3.1. CS1 Environment Contributing Scenario: Wet Polymerization (ERC5)

Release route	Release rate	Release evaluation method
Water	0.666 kg/day	spERC
Air	8.325 kg/day	spERC
Ground	0.01 %	spERC

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.001 mg/l	N.d.	0.279
fresh water sediment	121.3 mg/kg dry weight	N.d.	0.279
sea water	0.0001251 mg/l	N.d.	0.288
Marine sediment	12.51 mg/kg dry weight	N.d.	0.288
agricultural land	7.992 mg/kg dry weight	N.d.	0.292
environmentally exposed people - Inhalation	0.002 mg/m <sup>3</sup>	N.d.	< 0.01
environmentally exposed people - Oral	208.8 mg/kg bw/day	N.d.	372.8
All ways	N.d.	N.d.	372.8

### 3.2. Contributing Scenario CS2 - Worker: Curing (PROC4)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.17 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.044
skin contact, systemic, long-term	0.009 mg/kg bw/day	ECETOC TRA worker v2.0	0.008
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.051

### 3.3. Contributing Scenario CS3 - Spraying: Dermal Exposure Assessment (PROC7)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.21 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.054
skin contact, systemic, long-term	0.027 mg/kg bw/day	ECETOC TRA worker v2.0	0.024
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.078

### 3.4. Contributing Scenario CS4 - Spraying: Inhalation Exposure Assessment (PROC7)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.21 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.054
skin contact, systemic, long-term	0.027 mg/kg bw/day	ECETOC TRA worker v2.0	0.024
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.078

### 3.5. Contributing Scenario CS5 - Worker: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.085 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.022
skin contact, systemic, long-term	0.009 mg/kg bw/day	ECETOC TRA worker v2.0	0.008
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.03

### 3.6. Contributing Scenario CS6 - Worker: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.17 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.044
skin contact, systemic, long-term	0.009 mg/kg bw/day	ECETOC TRA worker v2.0	0.008
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.051

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## GENERALIZED USE BY PROFESSIONAL OPERATORS

### 1. TITLE SECTION

**Exposure scenario name:** Industrial production of varnishes and enamels - Industrial application of coatings and paints - Use in rigid foam, coatings, adhesives and sealants - Use in composite and foundry materials

**Date - Version:** 03/12/2020 - 1.0

**Life cycle stage:** Use at industrial sites

**Main user group:** Generalized use by professional traders

**Sector(s) of use:** Professional uses (SU22)

#### **Contributing scenario - Environment**

**CS1 Wet polymerization:** ERC8C

#### **Contributing scenario - Worker**

**CS2 Blend Operations:** PROC5

**CS3 Material Transfers:** PROC8b

**CS4 Material Transfers:** PROC9

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. CS1 Environment Contributing Scenario: Wet Polymerization (ERC8c)

**Environmental release categories:** Widespread use resulting in an inclusion into or onto the surface of an article (indoor use) (ERC8c)

##### **Product features (article)**

**Physical form of the product:** Liquid

##### **Amount used, frequency and duration of use**

**Amounts used:** Daily quantity at site 0.0005494 tons/day

##### **Conditions and measures for the municipal sewage treatment plant**

**Type of sewage treatment plant (STP):** Municipal STP - Water: minimum efficiency of 91.34%

**STP effluent (m<sup>3</sup>/day):** 2000

##### **Conditions and measures for waste treatment (including the product waste)**

**Waste treatment:** No specific measures identified.

##### **Other operational conditions affecting environmental exposure**

**Flow rate of receiving surface water:** 18000 m<sup>3</sup>/day

#### 2.2. Contributing Scenario CS2 - Worker: Blending Operations (PROC5)

**Process categories:** Mixing or Blending in Batch Processes (PROC5)

##### **Product features (article)**

**Physical form of the product:** Liquid

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

##### **Amount used, frequency and duration of use/exposure**

**Duration:** Covers a daily exposure up to 4 hours.

##### **Measures and technical-organizational conditions**

**Technical organizational measures:**

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Ensure personnel are trained to minimize exposure.

##### **Conditions and measures for personal protection, hygiene and health verification**

**Personal protective equipment:**

Wear an appropriate apron to avoid skin exposure.

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency 95 %



### ***Other operational conditions affecting worker exposure***

Indoor use

**Temperature:** A process temperature of up to 40°C is assumed

**Body parts exposed:** Possible skin contact is believed to be limited to the hands.

## **2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)**

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

### ***Product features (article)***

**Physical form of the product:** Liquid

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### ***Amount used, frequency and duration of use/exposure***

**Duration:** Covers a daily exposure up to 4 hours.

### ***Measures and technical-organizational conditions***

**Technical organizational measures:**

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Ensure personnel are trained to minimize exposure.

### ***Conditions and measures for personal protection, hygiene and health verification***

**Personal protective equipment:**

Wear an appropriate apron to avoid skin exposure.

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency 95 %

### ***Other operational conditions affecting worker exposure***

Indoor use

**Temperature:** A process temperature of up to 40°C is assumed

**Body parts exposed:** Possible skin contact is believed to be limited to the hands and forearms.

## **2.4. CS4 Worker Contributing Scenario: Material Transfers (PROC8b)**

**Process categories:** Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

### ***Product features (article)***

**Physical form of the product:** Liquid

**Concentration of the substance in the product:** Includes substance shares in the product up to 25%

### ***Amount used, frequency and duration of use/exposure***

**Duration:** Covers a daily exposure up to 4 hours.

### ***Measures and technical-organizational conditions***

**Technical organizational measures:**

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Ensure personnel are trained to minimize exposure.

### ***Conditions and measures for personal protection, hygiene and health verification***

**Personal protective equipment:**

Wear an appropriate apron to avoid skin exposure.

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency 95 %

### ***Other operational conditions affecting worker exposure***

Indoor use

**Temperature:** A process temperature of up to 40°C is assumed

**Body parts exposed:** Possible skin contact is believed to be limited to the hands and forearms.



### 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

#### 3.1. CS1 Environment Contributing Scenario: Wet Polymerization (ERC8c)

Release route	Release rate	Release evaluation method
Water	0.008 kg/day	spERC
Air	0 %	spERC
Ground	0 %	spERC

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	7.3E-05 mg/l	N.d.	0.017
fresh water sediment	7.301 mg/kg dry weight	N.d.	0.017
sea water	1.113E-05 mg/l	N.d.	0.026
Marine sediment	1.113 mg/kg dry weight	N.d.	0.026
agricultural land	7.318 mg/kg dry weight	N.d.	0.084
environmentally exposed people - Inhalation	9.158E-07 mg/m <sup>3</sup>	N.d.	< 0.01
environmentally exposed people - Oral	190.8 mg/kg bw/day	N.d.	340.7
All ways	N.d.	N.d.	340.7

#### 3.2. Contributing Scenario CS2 - Worker: Blending Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.714 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.183
skin contact, systemic, long-term	0.171 mg/kg bw/day	ECETOC TRA worker v2.0	0.156
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.339

#### 3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.714 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.183
skin contact, systemic, long-term	0.171 mg/kg bw/day	ECETOC TRA worker v2.0	0.156
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.339

### 3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.714 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.183
skin contact, systemic, long-term	0.171 mg/kg bw/day	ECETOC TRA worker v2.0	0.156
combined routes, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.339

### 4 GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

# Propylidyntrimethanol, propoxylated, reaction products with ammonia

## Substance identification

CAS number: 39423-51-3

## PROFESSIONAL USES

### 1. TITLE SECTION

Exposure scenario name: Professional uses.

Date - Version: 05/17/2023 - 3.0

#### Contributing scenario - Environment

SC1 Wide dispersive external use resulting in being included in item (Indoors) ERC8c

SC2 Wide dispersive external use resulting in being included in item (In outdoor environments) ERC8f

#### Contributing scenario - Worker

SC3 Mixing or blending in batch processes PROC5

SC4 Transfer of a substance or mixture (charging/discharging) at non-dedicated facilities PROC8a

SC5 Transfer of a substance or a mixture (charging/discharging) at dedicated facilities PROC8b

SC6 Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC9

SC7 Application with rollers or brushes PROC10

SC8 Non-industrial spraying PROC11

SC9 Treatment of articles by dipping and pouring PROC13

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. Environmental exposure control: Wide dispersive external use resulting in being included in item (Indoors) - ERC8c

##### Amounts used (or contained in item), frequency and duration of use/exposure

Yearly amount used in EU: 999 tons/year

Daily amount per site: 0,547397 kg/day

Fraction of EU tonnage used in region: 0.1

Maximum allowable site tonnage (Msafe): Daily amount per site 2004,1 kg/day

Critical compartment for Msafe: Risk from environmental exposure is determined by microbes in the wastewater treatment plant.

Maximum allowable site tonnage (Msafe): Daily amount per site 7.2 kg/day

Critical compartment for Msafe: Risk from environmental exposure is driven by fresh water, freshwater sediment, marine water and marine water sediment.

Maximum allowable site tonnage (Msafe): Daily amount per site 10.9 kg/day

Critical compartment for Msafe: Risk from environmental exposure is driven by soil.

Maximum allowable site tonnage (Msafe): Daily amount per site 23924.1 kg/day

Critical compartment for Msafe: Risk from environmental exposure is determined by humans through indirect exposure (mainly from ingestion).

Days of emission: 365

##### Conditions and measures for the waste water treatment plant

Type of STP: Municipal wastewater treatment plant

STP effluent: 2000m<sup>3</sup>/day

##### Other conditions affecting environmental exposure

Water flow on the receiving surface: 18 000 m<sup>3</sup>/day

Local fresh water dilution factor: 10

Local seawater dilution factor: 100

#### 2.2. Environmental exposure control: Wide dispersive external use resulting in being included in item (In outdoor environments) - ERC8f

##### Amounts used (or contained in item), frequency and duration of use/exposure

Yearly amount used in EU: 999 tons/year

Daily amount per site: 0,547397 kg/day

Fraction of EU tonnage used in region: 0.1

Maximum allowable site tonnage (Msafe): Daily amount per site 7.2 kg/day

Critical compartment for Msafe: Risk from environmental exposure is driven by fresh water, freshwater sediment, marine water and marine water sediment.

Maximum allowable site tonnage (Msafe): Daily amount per site 15.4 kg/day

Critical compartment for Msafe: Risk from environmental exposure is driven by soil.

Maximum allowable site tonnage (Msafe): Daily amount per site 23924.1 kg/day

Critical compartment for Msafe: Risk from environmental exposure is determined by humans through indirect exposure (mainly from ingestion).

Days of emission: 365

##### Conditions and measures for the waste water treatment plant

Type of STP: none

##### Other conditions affecting environmental exposure

Water flow on the receiving surface: 18 000 m<sup>3</sup>/day

Local fresh water dilution factor: 10

Local seawater dilution factor: 100

### 2.3. Worker Exposure Control: Mixing or blending in batch processes - PROC5

#### **Product features (article)**

**Physical form of the product:** Liquid blend

**Vapour pressure:** 0.0023 Pa

**Temperature:** 20°C

#### **Amounts used (or contained in item), frequency and duration of use/exposure**

**Duration:** Frequency and duration of use 480 min

**Frequency of use:** 5 days/week

#### **Organizational and technical measures and conditions**

Local exhaust ventilation

**Inhalation** - minimum yield of 80%.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Inhalation** - minimum yield of 30%.

#### **Conditions and measures for personal protection, hygiene and health assessment**

Wear suitable respirator.

**Inhalation** - minimum yield of 95 %

Wear chemically resistant gloves in combination with employee training. (EN374)

**Dermal** - minimum efficiency of 80%.

#### **Other conditions affecting worker exposure**

**Body parts exposed:** Palms 480 cm<sup>2</sup>

**Indoor and outdoor use:** Inside.

**Industrial or professional environments:** Professional use.

**Temperature:** 20 °C

### 2.4. Worker Exposure Control: Transfer of a substance or mixture (charging/discharging) at non-dedicated facilities - PROC8a

#### **Product features (article)**

**Physical form of the product:** Liquid blend

**Vapour pressure:** 0.0023 Pa

**Temperature:** 20°C

#### **Amounts used (or contained in item), frequency and duration of use/exposure**

**Duration:** Frequency and duration of use 240 min

**Frequency of use:** 5 days/week

#### **Organizational and technical measures and conditions**

Local exhaust ventilation

**Inhalation** - minimum yield of 80%.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Inhalation** - minimum yield of 30%.

#### **Conditions and measures for personal protection, hygiene and health assessment**

Wear suitable respirator.

**Inhalation** - minimum yield of 90 %

Wear chemically resistant gloves in combination with employee training. (EN374)

**Dermal** - minimum efficiency of 80%.

#### **Other conditions affecting worker exposure**

**Body parts exposed:** Both hands 960 cm<sup>2</sup>

**Indoor and outdoor use:** Inside.

**Industrial or professional environments:** Professional use.

**Temperature:** 20 °C

### 2.5. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities - PROC8b

#### **Product features (article)**

**Physical form of the product:** Liquid blend

**Vapour pressure:** 0.0023 Pa

**Temperature:** 20°C

#### **Amounts used (or contained in item), frequency and duration of use/exposure**

**Duration:** Frequency and duration of use 240 min

**Frequency of use:** 5 days/week

#### **Organizational and technical measures and conditions**

Local exhaust ventilation

**Inhalation** - minimum yield of 90 %

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Inhalation** - minimum yield of 30%.

#### **Conditions and measures for personal protection, hygiene and health assessment**

Wear chemically resistant gloves (EN374)

**Dermal** - minimum efficiency of 80%.

#### **Other conditions affecting worker exposure**

**Body parts exposed:** Both hands 960 cm<sup>2</sup>

**Indoor and outdoor use:** Inside.

**Industrial or professional environments:** Professional use.

**Temperature:** 20 °C

## 2.6. Worker Exposure Control: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - PROC9

### **Product features (article)**

**Physical form of the product:** Liquid blend

**Vapour pressure:** 0.0023 Pa

**Temperature:** 20 °C

### **Amounts used (or contained in item), frequency and duration of use/exposure**

**Duration:** Frequency and duration of use 240 min

**Frequency of use:** 5 days/week

### **Organizational and technical measures and conditions**

Local exhaust ventilation

**Inhalation** - minimum yield of 90 %

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Inhalation** - minimum yield of 30%.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear suitable respirator.

**Inhalation** - minimum yield of 90 %

### **Other conditions affecting worker exposure**

**Body parts exposed:** Palms 480 cm<sup>2</sup>

**Indoor and outdoor use:** Inside.

**Industrial or professional environments:** Professional use.

**Temperature:** 20 °C

## 2.7. Worker Exposure Control: Application with rollers or brushes - PROC10

### **Product features (article)**

**Physical form of the product:** Liquid blend

**Vapour pressure:** 0.0023 Pa

**Temperature:** 20 °C

### **Amounts used (or contained in item), frequency and duration of use/exposure**

**Duration:** Frequency and duration of use 480 min

**Frequency of use:** 5 days/week

### **Organizational and technical measures and conditions**

Local exhaust ventilation

**Inhalation** - minimum yield of 80%.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Inhalation** - minimum yield of 30%.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear suitable respirator.

**Inhalation** - minimum yield of 95 %

Wear chemically resistant gloves in combination with employee training. (EN374)

**Dermal** - minimum efficiency of 80%.

### **Other conditions affecting worker exposure**

**Body parts exposed:** Both hands 960 cm<sup>2</sup>

**Indoor and outdoor use:** Inside.

**Industrial or professional environments:** Professional use.

**Temperature:** 20 °C

## 2.8. Worker Exposure Control: Non-industrial spraying - PROC11

### **Product features (article)**

**Physical form of the product:** Liquid blend

**Vapour pressure:** 0.0023 Pa

**Temperature:** 20 °C

### **Amounts used (or contained in item), frequency and duration of use/exposure**

**Duration:** Frequency and duration of use 60 min

**Frequency of use:** 5 days/week

### **Organizational and technical measures and conditions**

Local exhaust ventilation

**Inhalation** - minimum yield of 80%.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Inhalation** - minimum yield of 30%.

### **Conditions and measures for personal protection, hygiene and health assessment**

Wear suitable respirator.

**Inhalation** - minimum yield of 95 %

Wear chemically resistant gloves in combination with employee training. (EN374)

**Dermal** - minimum efficiency of 90%.

### **Other conditions affecting worker exposure**

**Body parts exposed:** 1500 cm<sup>2</sup> (both hands and forearms)

**Indoor and outdoor use:** Inside.

**Industrial or professional environments:** Professional use.

**Temperature:** 20 °C

## 2.9. Worker Exposure Control: Treatment of articles by dipping and pouring - PROC13

### Product features (article)

Covers percentage substance in the product up to 25 %.

**Physical form of the product:** Liquid blend

**Vapour pressure:** 0.0023 Pa

**Temperature:** 20 °C

### Amounts used (or contained in item), frequency and duration of use/exposure

**Duration:** Frequency and duration of use 480 min

**Frequency of use:** 5 days/week

### Organizational and technical measures and conditions

Local exhaust ventilation

**Inhalation** - minimum yield of 80%.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Inhalation** - minimum yield of 30%.

### Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

**Inhalation** - minimum yield of 95 %

Wear chemically resistant gloves in combination with employee training. (EN374)

**Dermal** - minimum efficiency of 80%.

### Other conditions affecting worker exposure

**Body parts exposed:** Palms 480 cm<sup>2</sup>

**Indoor and outdoor use:** Inside.

**Industrial or professional environments:** Professional use.

**Temperature:** 20 °C

## 3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

### 3.1. Environmental release and exposure: Wide dispersive external use resulting in being included in item (Indoors) - ERC8c

Release route	Release rate%	Release evaluation method
Water	1	Environmental Release Category (ERC)
Air	15	Environmental Release Category (ERC)
Soil	0	Environmental Release Category (ERC)

Protection target	Estimated exposure	RCR
Sewage treatment plant	0.0027313mg/l	< 0.001
Fresh water	0.0003326mg/l	0.076
Fresh water sediments	0.0016965mg/kg dry weight	0.076
Sea water	0.0000335mg/l	0.076
marine sediments	0.0001707mg/kg dry weight	0.076
Soil	0.0000958mg/kg dry weight	0.05
Secondary poisoning	0.0002765mg/kg body weight/day	< 0.001

### 3.2. Environmental release and exposure: Wide dispersive external use resulting in being included in item (In outdoor environments) - ERC8f

Release route	Release rate%	Release evaluation method
Water	1	Environmental Release Category (ERC)
Air	15	Environmental Release Category (ERC)
Soil	0.5	Environmental Release Category (ERC)

Protection target	Estimated exposure	RCR
Fresh water	0.0003332mg/l	0.076
Fresh water sediments	0.0016993mg/kg dry weight	0.076
Sea water	0.0000335mg/l	0.076
marine sediments	0.000171mg/kg dry weight	0.076
Soil	0.0000677mg/kg dry weight	0.036
Secondary poisoning	0.0002769mg/kg body weight/day	< 0.001

### 3.3. Worker exposure: Mixing or blending in batch processes - PROC5

**Exposure routes: Dermal**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.686 mg/kg body weight/day (EASY TRA v3.6)  
RCR: 0.171

**Exposure routes: Inhalation**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.003 mg/m<sup>3</sup> (EASY TRA v3.6)  
RCR: < 0.001

### 3.4. Worker exposure: Transfer of a substance or mixture (charging/discharging) at non-dedicated facilities - PROC8a

**Exposure routes: Dermal**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.686 mg/kg body weight/day (EASY TRA v3.6)  
RCR: 0.171

**Exposure routes: Inhalation**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.004 mg/m<sup>3</sup> (EASY TRA v3.6)  
RCR: < 0.001

### 3.5. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities - PROC8b

**Exposure routes: Dermal**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.686 mg/kg body weight/day (EASY TRA v3.6)  
RCR: 0.171

**Exposure routes: Inhalation**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.019 mg/m<sup>3</sup> (EASY TRA v3.6)  
RCR: 0.004

### 3.6. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - PROC9

**Exposure routes: Dermal**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 1.714mg/kg body weight/day (EASY TRA v3.6)  
RCR: 0.429

**Exposure routes: Inhalation**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.004 mg/m<sup>3</sup> (EASY TRA v3.6)  
RCR: < 0.001

### 3.7. Worker exposure: Application with rollers or brushes - PROC10

**Exposure routes: Dermal**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 1.371 mg/kg body weight/day (EASY TRA v3.6)  
RCR: 0.343

**Exposure routes: Inhalation**

Health effect: systemic  
Exposure indicator: Long-term  
Estimated exposure: 0.003 mg/m<sup>3</sup> (EASY TRA v3.6)  
RCR: < 0.001

### 3.8. Worker exposure: Non-industrial spraying - PROC11

**Exposure routes: Dermal**

Health effect: systemic

Exposure indicator: Long-term

Estimated exposure: 2.679 mg/kg body weight/day (EASY TRA v3.6)

RCR: 0.67

**Exposure routes: Inhalation**

Health effect: systemic

Exposure indicator: Long-term

Estimated exposure: 0.642 mg/m<sup>3</sup> (EASY TRA v3.6)

RCR: 0.13

### 3.9. Worker exposure: Treatment of articles by dipping and pouring - PROC13

**Exposure routes: Dermal**

Health effect: systemic

Exposure indicator: Long-term

Estimated exposure: 0.686 mg/kg body weight/day (EASY TRA v3.6)

RCR: 0.171

**Exposure routes: Inhalation**

Health effect: systemic

Exposure indicator: Long-term

Estimated exposure: 0.003 mg/m<sup>3</sup> (EASY TRA v3.6)

RCR: <0.001

## 4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.



# N,N-dimethyl-1,3-diaminopropane

Substance identification

Chemical Name: N,N-dimethyl-1,3-diaminopropane

CAS number: 109-55-7

## GENERALIZED USE BY PROFESSIONAL OPERATORS

### 1. TITLE SECTION

**Exposure scenario name:** Industrial application of coatings and paints

**Date - Version:** 17/03/2020 - 1.0

**Life cycle stage:** Generalized use by professional operators

**Main user group:** Professional uses

**Sector(s) of use:** Professional uses (SU22)

#### **Contributing scenario - Environment**

**CS1 Wet polymerization:** ERC8c

#### **Contributing scenario - Worker**

**CS2 Roller and brush application:** PROC10

### 2. CONDITIONS OF USE AFFECTING EXPOSURE

#### 2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8c)

**Environmental release categories:** Generalized use with subsequent inclusion in or on the surface of an article (indoor use) (ERC8c)

##### **Product features (article)**

**Physical form of the product:** Liquid

##### **Amount used, frequency and duration of use**

**Release Type:** Continuous release

**Issue days:** 365 days/year

##### **Measures and technical-organizational conditions**

**Used sewage treatment plant.**

Exhaust gas treatment with thermal oxidation.

Do not use sewage sludge with fertilizer. The sludge is disposed of or recovered.

Do not spread industrial sludge on natural soils. Aerobic biological treatment.

##### **Conditions and measures relating to municipal sewage treatment plants**

**Type of sewage treatment plant (STP):** Municipal STP

**STP effluent (m<sup>3</sup>/day):** 2000

##### **Other operational conditions affecting environmental exposure**

**Local seawater dilution factor:** 100

**Local fresh water dilution factor:** 10

**Flow rate of receiving surface water:** 18000 m<sup>3</sup>/day

#### 2.2. CS2 Contributing Scenario - Worker: Roller and brush application (PROC10)

**Process categories:** Roller and brush application (PROC10)

##### **Product features (article)**

**Physical form of the product:** Liquid

**Vapor pressure:** 590 Pa

**Concentration of the substance in the product:** Includes substance shares in the product up to 5%.

##### **Amount used, frequency and duration of use/exposure**

**Duration:** 240 min

**Frequency:** 5 days/week

### **Measures and technical-organizational conditions**

Provide supplementary ventilation to points where emissions occur. Inhalation - minimum efficiency of 80%.

Ensure that skin contact is avoided.

Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

Avoid direct contact with the product, even with contaminated hands.

Skin contact with the substance is to be excluded.

### **Conditions and measures related to personal protection, hygiene and health verification**

#### **Personal protective equipment:**

Wear adequate eye protection.

Wear suitable gloves, tested according to EN347.

Wear suitable respiratory protection. Inhalation - minimum efficiency of: 95 %

#### **Other operational conditions affecting worker exposure**

Indoor use

**Temperature:** Assumes a process temperature up to 20°C.

## **3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE**

### **3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8c)**

<b>Protection target</b>	<b>Degree of exposure</b>	<b>Calculation method</b>	<b>Risk characterization ratio (RCR)</b>
Marine sediment	19.1 kg/day	N.d.	0.001434

### **3.2. CS2 Contributing Scenario - Worker: Roller and brush application (PROC10)**

<b>Route of Exposure, Impact on Health, Exposure Indicator</b>	<b>Degree of exposure</b>	<b>Calculation method</b>	<b>Risk characterization ratio (RCR)</b>
by inhalation, systemic, short-term	0.5109 mg/m <sup>3</sup>	ECETOC TRA Worker v3	0.42575

## **4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO**

**Guidance to check compliance with the exposure scenario:** Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.